




REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN1610360~364	2016/01/11	Ruru	Change Logo & Note

F
E
D
C
B
A




BD-08AFFM-LR7AXX
XX:01~99Meter
01:01Meter
02:02Meters
...
99:99Meters
Cable Length(L):01~99Meters



Pin Assignments
Front View

8	Green
7	Yellow
6	Orange
5	Red
4	Blue
3	White
2	Brown
1	Black
Conn.	Wire Color
Pin Out	



- Note:
- * @CImportant Dimension To Check.
 - * Waterproof Rate:IP67
 - * Housing: Nylon+GF,Black
 - * Pin: Copper Alloy,Gold Plated
 - * Cable: UL2464 24AWG*8C+Drain+Al/My,Black PVC Jacket UV Resistant, OD=5.5
 - * Cable Length Tolerance: 01M: ±40mm
02M~05M: ±60mm
06M~10M: ±100mm
11M~30M: ±200mm
31M~99M: ±500mm

UNIT:mm	TOLERANCE ±0.5 mm		TITLE Standard,Cable Lock 8Pin F Conn F Pin		ITEM NO		DRAWN BY Ruru		DATE 2016/01/11	
SCALE Free			SHEET 1 OF 1		DWG NO BD-08AFFM-LR7AXX		CHECKED BY Rita		DATE 2016/01/11	
REV. B			SIZE A4		CUSTOMER ALTW		APPROVED BY Lisa		DATE 2016/01/11	
QC :Inspection Item									8 FMW0702-01-01A2	

Amphenol LTW
安費諾亮泰企業股份有限公司

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.