


TITLE: 6 W 12.4GHz SMA/m COAXIAL TERMINATION

LTR. B

DRAWING



General tolerances: +/- 0.5 mm

ELECTRICAL CHARACTERISTICS


FREQUENCY RANGE	: DC - 12.4GHz
IMPEDANCE	: 50 Ohms
DC RESISTANCE	: 50 Ohms $\pm$ 5 %
AVERAGE POWER HANDLING	: 6 W at 75°C
PEAK POWER HANDLING	: 4 kW (1 μ s, 1%.) at 25°C
V.S.W.R :	DC - 4 GHz : $\leq$ 1.10
	4 - 8 GHz : $\leq$ 1.20
	8 - 12.4 GHz : $\leq$ 1.30

MECHANICAL CHARACTERISTICS

CONNECTOR	: SMA male per MIL C 39012
MAXIMUM WEIGHT	: 22 grams

ENVIRONMENTAL CHARACTERISTICS

OPERATING TEMPERATURE RANGE (°C)	: -55 , +125
STORAGE TEMPERATURE RANGE (°C)	: -55 , +125



Tentative data subject to change without notice

PEN CAT	QUALITY Dpt App.					
			B	New format	22.10.92	PG
			A1	New format	21.03.89	KL
PAGE 1 / 1	DATE 25.11.83	NAME DP	LTR	REVISIONS	DATE	APP.