

Technical drawing of a mechanical part, likely a connector or plug, showing dimensions in millimeters. The drawing includes a side view and a cross-sectional view. Dimensions are: 3.3 ± 0.1, 2.3 ± 0.15, 6, 5, 4.5, 4.5 ± 0.15, 0.7.

Technical drawing of a metal bracket. The drawing shows a top view and a side view. The top view is a rectangle with a central slot. The dimensions are: total length 100mm, total width 10mm, and a central slot width of 10mm. The side view shows a height of 10mm and a base width of 10mm. The drawing is labeled with dimensions in millimeters (mm).

VERSION B	2-927836-2	C	CuSn4		0.5 - 1.0 FLR	E = 2.8	H = 7.6	0.5mm² = 1.43	MQC - Applicator 878337-2	539635-1 WITH DIE: mit Matrize 739736-2	3	5.4	7.2	20	1.25	963243-1 963244-1	100132-1
	12-1-927836-2	C	CuFe2			G = 3.0	K = 7.7	0.75mm² = 1.52									
	927836-7	C	CuSn4	vorverzinkt PRETINNED		D = 1.1	D = 5.6	1.0mm² = 1.61									
	927836-1	C	CuFe2														
	2-927835-2	C	CuSn4		>1.0 - 2.5 FLR	E = 3.8	H = 7.6	1.5mm² = 1.76	MQC - Applicator 878338-2	539635-1 WITH DIE: mit Matrize	3.5	5.9	7.7	20	1.25	963244-1 963245-1	100132-1
	2-927835-1	C	CuSn4			G = 4.1	K = 7.7	2.0mm² = 1.90									
	1-927835-3	C	CuFe2			D = 1.6	D = 5.6	2.5mm² = 2.04									
	12-1-927835-2	C	CuFe2														
	927835-7	C	CuFe2		>2.5 - 4.0 FLR	E = 4.6	H = 7.6	3.0mm² = 2.13	MQC - Applicator 878441-2	539635-1 WITH DIE: mit Matrize	4	5.9	7.7	20	1.25	963245-1	100132-1
	927835-2	C	CuSn4	vorverzinkt PRETINNED		G = 4.8	K = 7.7	-									
	927835-1	C	CuFe2			D = 2.4	D = 5.6	4.0mm² = 2.35									
	2-928966-2	D	CuSn4			>3.0 - 5.0 FLR	E = 4.8 G = 5.2 D = 2.5	H = 8.15 K = 7.8 D = 6.0		3.0mm² = 2.25 4.0mm² = 2.50 5.0mm² = 2.75							
	2-928966-1	D	CuSn4	vorverzinkt PRETINNED													
	1-928966-3	D	CuFe2														
	12-1-928966-2	D	CuFe2														
	928966-7	D	CuFe2														
928966-2	D	CuSn4	vorverzinkt PRETINNED														
928966-1	D	CuFe2															
1241962-1	B	CuFe2	vorverzinkt PRETINNED	>3.0 - 5.0 FLR	E = 4.8 G = 5.2 D = 2.5	H = 8.15 K = 7.8 D = 6.0	3.0mm² = 2.25 4.0mm² = 2.50 5.0mm² = 2.75	MQC - Applicator -	WITH DIE: mit Matrize	4	5.9	7.7	20	1.25	967011-1 963245-1	100132-1	
TE Connectivity ORDER - MD STRIP FORM Bandware	REV	MATERIAL Werkstoff	SURFACE Oberfläche	DBG WIRE RANGE (mm²)	WIRE CRIMP Drantsrimp	INSUL-CRIMP Isol. - crimp	CRIMP HEIGHT Crimp-Höhe	APPLICATION TOOL Anschlag-WKZ	HAND TOOL Handzange	A	B	C	D	E	SINGLE WIRE SEAL Einzeldichtung	DEAD END PLUG Blindstopfen	
					CRIMP DIMENSIONS (mm) Crimpbmessungen (mm)			EXTRACTION TOOL Auszugwerkzeug Nr. 726503-1								TE CONNECTIVITY ORDER - No.	

Technical drawing of a U-shaped component. The drawing shows a cross-section of the component, which is U-shaped with a central circular hole. The dimensions are specified as follows:

- $H \pm 0.3$: Total height of the component.
- $k \pm 0.3$: Height of the side flange.
- $\varnothing D \pm 0.1$: Diameter of the central hole.

12 OBSOLETE

SECTION B-B
Schnitt B-B