





JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
E6522	6.0	.030	.025	0.31	10,000	C-2V
E79	6.0	.200	.600	7.54	1,000	C-2R
E84	6.3	.040	.030	0.40	20,000	C-2V
E86	6.3	.200	.400	5.03	20,000	C-2V
E12522	12.0	.030	.045	0.57	10,000	C-2F
E21203A	12.0	.100	.640	8.04	2,000	C-2V
E73	14.0	.080	.300	3.77	15,000	C-2V
E37	14.0	.090	.500	6.29	1,500	C-2F
E74	14.0	.100	.720	9.05	1,000	C-2V
E13522	24.0	.030	.160	2.01	5,000	C-2F
E85	28.0	.040	.300	3.77	10,000	C-2F
E17	28.0	.065	.650	8.17	5,000	C-2F

METRIC



THIRD ANGLE PROJECTION

DIMENSIONS ARE IN MILLIMETERS

TOLERANCE UNLESS OTHERWISE SPECIFIED

1 PL +/- 0.2
2 PL +/- 0.20
ANGLE +/- 0

JKL

COMPONENTS CORPORATION

TITLE

T-1 1/2 STANDARD GLASS WEDGE BASE

C DELETE * NOTE 7/6/11

B ADD DIM OVER WIRE, E84 LUMENS TO 0.40 12/1/10

A Pb FREE NOTE ADDED 8/25/04

RELEASED & CANCEL GW-STD-T1 1/2 5/5/00

REV. NO. DESCRIPTION/ECO NUMBER APPVD DATE

DRAWN BY L. WENGSTROM

APPVD BY L.W. DATE 7/6/11

- CAD DRAWING -
MANUAL REVISIONS NOT PERMITTED

SIZE A

FSCM NO. 55335

DRAWING NO.

GLASS WEDGE BASE T-1 1/2

SCALE NONE

RELEASED DATE 5/5/00

REVISION DATE 7/6/11

REV. NO. C

SHEET 1 OF 1