







THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.


REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN-8B0301	2008/09/17	Shin	Add Note and Update Drawing to New Format
C	LEN1730275	2017/03/17	Ruru	Change Logo
D	CI90274	2019/02/19	Ruru	Modify Note



Pin Assignments
Front View



Recommended Panel Cut-Out



- Note:
- * Important Dimensions To Check.
 - * Waterproof Rate: IP67, Unmated
 - * Housing: Thermoplastic, Black
 - * Pin: Copper Alloy, Gold Plated
 - * Nut: Thermoplastic, Black
 - * Gasket: Rubber, Black
 - * Use with Waterproof Cap or Dustcap
Panel Thickness Max: 3.0mm
 - * Use without Waterproof Cap or Dustcap
Panel Thickness Max: 4.5mm
 - * Gasket and Nut are packed separately in PE bags.

UNIT:mm		TOLERANCE		TITLE		ITEM NO		DRAWN BY		DATE	
.X ±0.25		.XX ±0.1		Standard,Panel Lock 3Pin M Conn F Pin		BB-03PMFP-LC7001		Ruru		2019-02-19	
.XXX ±0.05		ANGLES ±1°		SCALE 1:1		DWG NO BB-03PMFP-LC7001		CHECKED BY Rita		DATE 2019-02-19	
REV. D		WC-REV. A.3		SIZE A4		CUSTOMER ALTW		APPROVED BY Max		DATE 2019-02-19	
				SHEET 1 OF 1							
				QC: Inspection item							

Amphenol LTW
安費諾亮泰企業股份有限公司