



Reliable

Efficient

Intelligent

Universal Input, Universal Output. Reliable and Long Lasting with No Flicker

The Cita Technologies CPWLD 13 is a conservatively rated, highly reliable, all-weather LED driver specifically suited for the modern demands of commercial solid state lighting. A universal input / output design adapts to a wide range of line and string voltages, allowing for worldwide implementation from a single SKU. Fully variable Multiple Dimming Control delivers analog-like smoothness with zero flicker. Cita is proud to design and manufacture all of its own LED drivers, and stands behind them with a 5 year limited warranty.

KEY FEATURES:

- **Universal Input and Output (100VAC - 305VAC)**
- **Excellent 0-10V dimming performance with no flicker**
- **Compatible with IEC 60929:2006 - 0-10V ballast controls**
- **Ultra compact design**
- **Product Assurance: 5 Year Limited Warranty**
(see warranty terms for more information)
- Smooth light output promotes longer LED life
- Fully optimized design produces clean waveforms, reducing noise and stress on components.
- Multiple Dimming control interface
- Fully potted design meets UL IP67
- Highly reliable in wet locations
- Excellent protection features with auto recovery for all conditions
- Long Lifetime Expectancy: >100K hours @ 50°C ambient / full load
- Low standby (Off) power: 0.6W @ 120VAC; 1.5W @ 230VAC

APPLICATIONS:

Wide Variety of LED lighting fixtures:

- Indoor and outdoor
- Dimming and non dimming
- Industrial, commercial, and residential
- Worldwide acceptance
- Wireless mesh network ready



UL INFORMATION:

- 13W LED Driver
CC up to 1050mA, 60VDC
CV up to 1050mA, 12V-60VDC
- EN60950-1, 2nd Edition, Class 2, IP67
- UL File: E354816

ORDERING INFORMATION:

- CPWLD 13-18U-070:
12-22VDC / 700mA / Dimming
- CPWLD 13-36U-035:
12-42VDC / 350mA / Dimming
- CPWLD 13-xxU-yyy:
Custom CC models
- CPWLD 13-zz-00:
Custom CV Models
zz = 12, 24, 36, 48, 60 or upon request

CITA Technologies, L.L.C.

975 Deerfield Pkwy, Buffalo Grove, Illinois 60089, USA

T: 1-800-503-9180 or 1-847-419-9118 F: 1-847-419-1515



citapower.com

Operating Specifications

Electrical		Environmental	
Input Voltage Range	100 - 305VAC (47-63Hz)	Operating Temperature	-30°C to +70°C
Input Power	Max 16W	Case Temperature	+90°C maximum
Isolation	3000VAC / 1 minute	Storage Temperature	-40°C to +105°C
Inrush Current	60A at 230VAC, 25°C cold start	Ingress Protection	IP67
Power Factor	60% Typical	Case Material	UL94V-0 Plastic (F1)
Output Voltage Range	-035 version: 350mA +/-2%, 12-36VDC, 4-12 LED string -070 version: 700mA +/-2%, 12-18VDC, 4-5 LED string All models with turn off capability (DIM <1V)	Safety Agency Approvals	
Output Power	Max 13W		
Auxiliary Output	No Aux Output	EN60950-1, 2nd edition, Class 2, IP67, for wet location use UL file number: E354816, standards: UL 60950-1, 2nd Edition CSA C22.2 No. 60950-1-07, 2nd Edition	
Efficiency	Typical, full load, 13W = 83% Typical, min. LED string (5), or at -30°C = 70%		
MTBF	>500,000 hours @ 50°C ambient, full load	CB Certificate No: E354816-A1-CB-1, Standards: IEC 60950-1(ed.2), IEC 60950 1(ed.2);am1 EN 60950-1:2006/ A11:2009/ A1:2010/ A12:2011 EMI Standards: CE, EN 55022, Class B; FCC Part 15, Class B	
Lifetime	>100,000 hours @ 50°C ambient, full load >27,000 hours @ 70°C ambient, full load		
Dimming Control	0-10VDC (10% to 100% dimming) 0-10VDC dimming compatible with IEC60929:2006 controllable ballasts Potentiometer PWM dimming (1KHz/10VDC)		
Robust Protection	OVP, OCP, SCP, OTP		
Mechanical			
Main Body Size	L x W x H: 3.37" x 1.46" x 0.98" Weight: 0.30 lb See drawing below for details		

Notes:

1. This product is not intended to function with TRIAC dimmer
2. Wire Leads: Input: 18AWG, 105°C, 600V; Output: 22AWG, 105°C, 600V



XX: Nominal voltage: 12-56VDC
 YYY: Nominal constant current (mA)
 AA: Open circuit or maximum voltage: 15-60VDC
 BBB: Nominal constant current
 yywwC: Date code yyww, followed by letter "C" for mfg location
 Z: Product revision

CITA Technologies, LLC
 975 Deerfield Pkwy, Buffalo Grove, Illinois 60089, USA
 T: 1-800-503-9180 or 1-847-419-9118 F: 1-847-419-1515
 www.citatechllc.com