

Between-Series Adapters

N Flange Mount to SMA

N Flange Mount Male Plug to SMA Male Plug

Model Number

ADT-2576-NM-SMM-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz


VSWR: 1.04 @ DC-4.0 GHz

1.07 @ 4.0-8.0 GHz

1.12 @ 8.0-18.0 GHz

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



N Flange Mount Male to SMA Female Jack

Model Number

ADT-2577-NM-SMF-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz


VSWR: 1.04 @ DC-4.0 GHz

1.07 @ 4.0-8.0 GHz

1.12 @ 8.0-18.0 GHz

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



N Flange Mount Female to SMA Male Plug

Model Number

ADT-2578-NF-SMM-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz


VSWR: 1.04 @ DC-4.0 GHz

1.07 @ 4.0-8.0 GHz

1.12 @ 8.0-18.0 GHz

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



Note: Also available with 1.23 O.A.L. as ADT-2578-MF-009-02

N Flange Mount Female to SMA Female Jack

Model Number

ADT-2579-NF-SMF-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz


VSWR: 1.04 @ DC-4.0 GHz

1.07 @ 4.0-8.0 GHz

1.12 @ 8.0-18.0 GHz

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



Note: Also available with 1.23 O.A.L. as ADT-2579-FF-012-02