

SPECIFICATION CONTROL DRAWING

82A1132TITLE RADIATION-CROSSLINKED, MODIFIED, FLUOROPOLYMER-INSULATED,
THREE CONDUCTOR CABLE, SHIELDED, JACKETED, LIGHTWEIGHT, FLEXIBLE


Date 04-27-04

Revision A

This specification sheet forms a part of the latest issue of Raychem Specification 80.

COMPONENT WIRES - 82A0112

SHIELD - SILVER-COATED COPPER

JACKET - RADIATION-CROSSLINKED,
MODIFIED FLEXIBLE ETFE

CABLE CONSTRUCTION DETAILS

PART NUMBER 1/	CONDUCTOR SIZE (AWG)	SHIELD SIZE (AWG)	JACKET THICKNESS (inches)		OUTSIDE DIAMETER (inches)		MAXIMUM WEIGHT (lb/1000 ft)
			MINIMUM	NOMINAL	NOMINAL	MAXIMUM	
82A1132-26-*	26	38	.006	.009	.106	.112	10.6
82A1132-24-*	24	38	.006	.009	.115	.121	13.4
82A1132-22-*	22	38	.006	.009	.128	.134	16.8
82A1132-20-*	20	38	.007	.010	.151	.159	22.8
82A1132-18-*	18	38	.008	.011	.177	.186	32.8
82A1132-16-*	16	38	.009	.013	.214	.224	47.3
82A1132-14-*	14	38	.010	.014	.259	.272	71.0
82A1132-12-*	12	38	.011	.016	.310	.326	102.
82A1132-10-*	10	36	.013	.019	.398	.418	171.
82A1132- 8-*	8	36	.016	.023	.488	.513	260.
82A1132- 6-*	6	34	.018	.026	.588	.617	394.
82A1132- 4-*	4	34	.024	.034	.781	.820	642.
82A1132- 2-*	2	34	.027	.039	.936	.982	941.
82A1132- 0-*	0	32	.036	.051	1.25	1.31	1527.

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 150°C

Maximum continuous conductor temperature

VOLTAGE RATING: 600 volts (rms) at sea level

CROSSLINKING PROOF TEST: 300 ± 3°C for 1 hour,

DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz

JACKET COLOR: White preferred

JACKET ELONGATION AND TENSILE STRENGTH:

Elongation, 100% (minimum)

Tensile Strength, 3000 lbf/in² (minimum)

JACKET FLAWS:

Spark Test, 1500 volts (rms)

Impulse Dielectric Test, 6.0 kV (peak)

SECANT MODULUS: 4.0 X 10⁴ lbf/in² (maximum),

2 % strain, 2 in. Jaw separation, 0.2 in. / minute,

procedural reference ASTM D 882

SHIELD COVERAGE: 85% (minimum)

VOLTAGE WITHSTAND (Post Environmental):

1000 volts (rms), 60 Hz, 1 minute

PART NUMBER

The "*" in the part numbers above shall be replaced by a color code designator with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color. Colors shown do not necessarily reflect the sequence of manufacturing.

1/ Example: AWG 20, black, brown and red component wires; white jacket: 82A1132-20-0/1/2-9

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.

DIMENSIONS ARE IN INCHES, AND UNLESS OTHERWISE DESIGNATED ARE NOMINAL.

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.
REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.

tyco
Electronics

Raychem Wire & Cable
501 Oakside Avenue
Redwood City, CA 94063-3800
Phone: 1-800-227-8816
Fax: 1-650-361-6297

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[82A1132-20-2/6/9-9](#) [82A1132-26-0/6/9-9](#)