

B9C172 Fiber - Armored Outdoor Central Tube



For more Information
please call

1-800-Belden1



General Description:

FiberExpress Central Tube Cable-Steel Corrugated Armor, 6-Fiber, OM3 OSP, Loose Tube, Outdoor Rated with UV Resistant Black Jacket, Fully waterblocked with gel-filled buffer tube, No rods - easy handling. Crush, impact and abrasion resistant.

Physical Characteristics (Overall)

Fiber Type:	50 Micron (OM3)
Number of Fibers:	6
Core Diameter:	50
Clad Diameter:	125
Primary Coating Material:	250
Buffer Tube Diameter:	0.15
Buffer Tube Material:	Thermoplastic
Buffer Tube Filling Material:	Gel

Outer Jacket

Outer Jacket Material:

Outer Jacket Material

PE - Polyethylene

Outer Jacket Diameter:

Nom. Dia. (mm)

7.874

Outer Jacket Color:	Black
---------------------	-------

Strength Member

Strength Member Material:	Aramid Yarn
---------------------------	-------------

Armor

Armor Type:	Corrugated
Armor Material:	Steel

Overall Cable

Overall Nominal Diameter:	12.192 mm
---------------------------	-----------

Mechanical Characteristics (Overall)

Storage Temperature Range:	-40°C To +75°C
Installation Temperature Range:	-30°C To +75°C
Operating Temperature Range:	-30°C To +75°C
Bulk Cable Weight:	141.379 Kg/Km
Min. Bend Radius/Minor Axis:	243.840 mm
Min. Bend Radius for Long Term Application:	182.880 mm
Max. Load for Installation:	2668.920 N
Max. Load for Long Term Application:	889.640 N

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	08/01/2008

METRIC MEASUREMENT VERSION

B9C172 Fiber - Armored Outdoor Central Tube

EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	No
Suitability - Outdoor:	Yes
Suitability - Aerial:	Yes - Black only, when supported by messenger wire.
Sunlight Resistance:	Yes

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Optical Characteristics (Overall)

Maximum Attenuation @ 850nm:	3.0 dB/km
Maximum Attenuation @ 1300nm:	1.0 dB/km
Minimum Bandwidth @ 850nm:	1500 MHz*km
Minimum Bandwidth @ 1300nm:	500 MHz*km
Maximum Gigabit Ethernet Length @ 850nm:	900 meters
Maximum Gigabit Ethernet Length @ 1300nm:	550 meters

Fiber Coding MLT EMEA:

Fiber/Tube No.	Color
1	Blue
2	Orange
3	Green
4	Brown
5	Slate
6	White
7	Red
8	Black
9	Yellow
10	Violet
11	Rose
12	Aqua

Related Documents:

[Loose Tube Central Tube Cable.pdf](#) - Loose Tube Central Tube Cable technical information.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
B9C172	1 FT	0.089 LB	BLACK		REPLACED BY FS3C00660

Revision Number: 1 Revision Date: 07-31-2013

© 2017 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.