

CONFIGURATION		PART NUMBER	
Female Receptacle, 4 Pin, 16Awg & 2.5mm , Shell 14		RT00142SNH	
DIMENSIONS			
<p>Technical drawings of the RT360 connector showing dimensions and components.</p> <p>Components labeled: O-Ring, Insert, Shell, Seal Gasket.</p> <p>Dimensions and features:</p> <ul style="list-style-type: none"> <li>Ø 20.70, Ø 22.20, 11.30, 1.80, 25.0, 13/16-20 UNEF</li> <li>MASTER KEYWAY, 4-Ø 3.20</li> <li>28.6, 23.00, 23.00, 28.6</li> <li>Ø 21.50 (For Front Panel Mounting)</li> <li>Ø 25.00 (For Rear Panel Mounting)</li> <li>4-Ø 3.20</li> <li>PANEL CUT OUT REFERENCE</li> </ul>			
TECHNICAL DATA			
TEMPERATURE RANGE:	-40°C to + 105°C		
PROTECTION:	IP67 in mated condition and in combination with sealed backshell		
VOLTAGE RATING:	350V		
HOUSING BODY:	Zinc Alloy, Nickel Plated		
COUPLING NUT:			
INSERT:	Glass-filled Thermoplastic UL94-V0		
SEAL:	NBR		
CURRENT:	2-16Awg at 13A and 2-2.5mm at 23A		
CONTACT SIZE:	16Awg & 2.5mm		
APPROVALS:	UL ECBT2		