9001KYG1Y





Main

Complementary

Product destination	For Ø 30 mm control and signalling units			
Material	Aluminium			
Colour of cover	Yellow			
Product weight	2.65 lb(US) (1.2 kg)			

Environment

protective treatment	TH	
ambient air temperature for storage	-40158 °F (-4070 °C)	<u></u>
ambient air temperature for operation	-13158 °F (-2570 °C)	
overvoltage category	II conforming to IEC 61140	
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 3 NEMA 4 NEMA 6	demonstrate of the produ

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1002 - Schneider Electric declaration of conformity	Compliant - since 1002 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Nickel compounds, which is known to the State of California to cause cancer, and	Nickel compounds, which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the Stat of California to cause birth defects or other reproductive harm.	eDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months	

Dimensions

