



MATERIAL: POLYESTER MLDG COMPOUND
FERRULE
COLOR: BLACK

—CAP
MATERIAL: POLYESTER MLDG COMPOUND
COLOR: RED

—#16 AWG Si INSULATED
LEAD WIRE
COLOR: WHITE

86.3534

1 TO MATE WITH AMP LGH 1/2L RECEPTACLE
WITH .89 [22.6] BARREL DEPTH

2 MARK PER MIL-STD-130.

3. OPERATING VOLTAGE: 15 KVDC AT 0 TO 70,000 FEET, -55°C TO 125°C .

4 PIGTAILS ARE SOLDER DIPPED.

5 INSULATION CUT, BUT NOT REMOVED.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN T.SHUEY 29-SEP-89		 TE Connectivity	
		CHK C.CHEHOVIN 09-OCT-89			
DIMENSIONS: INCHES [mm]		TOLERANCES, UNLESS OTHERWISE SPECIFIED:		NAME LEAD ASSY SGL END, POSITIVE STOP LGH-1/2L	
		APVD D.FABY 09-OCT-89			
1 PLC ± - 2 PLC ± - 3 PLC ± .02 [0.5] 4 PLC ± - ANGLES ± -		PRODUCT SPEC - APPLICATION SPEC -			
MATERIAL -		WEIGHT 0.000000			
FINISH -		CUSTOMER DRAWING		SIZE A2	
				CAGE CODE 00779	
				DRAWING NO C-863534	
				RESTRICTED TO -	
				SCALE 2:1	
				SHEET 1 of 1	
				REV J	