

## SPECIFICATION FOR APPROVAL

Customer.				
Description.	DC FAN			
Customer Part No		REV.		
Delta Model No	ASB03512HB-F00	REV. 01		
Sample Issue No				
Sample Issue Date	JAN-31-2018			
PLEASE SEND ONE COPY OF THIS SPECIFICATION BACK AFTER YOU SIGNED APPROVAL FOR PRODUC- TION PRE-ARRANGEMENT.				
APPROVED BY :				
DATE:				

Delta Electronics, Inc.

HeTianXia High-Tech Industrial Park.

Shi Jie Town, Dong Guan City.

Guangdong Province, China. P. R. C.

TEL: 86-769-86329008 FAX: 86-769-86631589 Delta Electronics, Inc. HeTianXia High-Tech Industrial Park. Shi Jie Town, Dong Guan City. Guangdong Province, China. P. R. C.

TEL: 86-769-86329008 FAX: 86-769-86631589

# 

NONE	
DESCRIPTION:	

Delta Electronics, Inc.

HeTianXia High-Tech Industrial Park.

Shi Jie Town, Dong Guan City.

Guangdong Province, China. P. R. C.

TEL: 86-769-86329008 FAX: 86-769-86631589

# 

Customer:			
Description:	DC FAN		
Customer P/N:		REV:	
Delta Model NO.:	ASB03512HB-F00	Delta Safety Model NO.: ASB03512	ΗВ
Sample Rev:	01	Issue N0:	
Sample Issue Date:	JAN-31-2018	Quantity:	

#### 1. SCOPE:

THIS SPECIFICATION DEFINES THE ELECTRICAL AND MECHANICAL CHARACTERISTICS OF THE DC BRUSHLESS AXIAL FAN.

#### 2. CHARACTERS:

ITEM	DESCRIPTION
RATED VOLTAGE	12 VDC
OPERATION VOLTAGE	5.0 - 13.8 VDC
STARTING VOLTAGE	5.0 VDC (MAX.)
RATED CURRENT	0.11 (MAX. 0.18) A (SAFETY CURRENT 0.18A)
RATED POWER	1.32 (MAX. 2.16) W
RATED SPEED	11000±15% R.P.M.
MAX. AIR FLOW   (AT ZERO STATIC PRESSURE)	0.270 (MIN. 0.230) M <sup>3</sup> /MIN. 9.507 (MIN. 8.081) CFM
MAX. AIR PRESSURE (AT ZERO AIRFLOW)	8.305 (MIN. 6.000) mmH <sub>2</sub> 0 0.327 (MIN. 0.236) inchH <sub>2</sub> 0
ACOUSTICAL NOISE (AVG.)	37.0 (MAX. 41.5)dB-A
INSULATION TYPE	UL: CLASS A
	<u></u>

(continued)


page: 1 A00

PART NO:
DELTA MODEL: ASB03512HB-F00

INSULATION STRENGTH	10 MEG OHM MIN. AT 500 VDC (BETWEEN FRAME AND (+) TERMINAL)	
DIELECTRIC STRENGTH	5 mA MAX. AT 500 VAC 50/60 Hz ONE MINUTE, (BETWEEN FRAME AND (+) TERMINAL)	
EXTERNAL COVER	OPEN TYPE	
LIFE EXPECTANCE (L10)	30,000 HOURS CONTINUOUS OPERATION AT 40°C WITH 65% RH.	
ROTATION	COUNTERCLOCKWISE DIRECTION FROM FRONT VIEW OF AIR FLOW INLET	
LEAD WIRE	UL 1061 AWG #26  RED WIRE POSITIVE(+)  BLACK WIRE NEGATIVE(-)  BLUE WIRE FREQUENCY(F00)	

NOTES:

- 1. ALL READINGS ARE MEASURED AFTER STABLY WARMING UP THROUGH 10 MINUTES
- 2. STANDARD AIR PROPERTY IS AIR AT (Td) 25°C TEMPERATURE, (RH) 65% RELATIVE HUMIDITY, AND (Pb) 760 mmHg BAROMETRIC PRESSURE.
- 3. THE VALUES WRITTEN IN PARENS, ( ), ARE LIMITED SPEC.
- 4. ACOUSTICAL NOISE MEASURING CONDITION:



NOISE IS MEASURED AT RATED VOLTAGE IN FREE AIR IN SEMI-ANECHOIC CHAMBER WITH B & K SOUND LEVEL METER WITH MICROPHONE AT A DISTANCE OF ONE METER FROM THE FAN INTAKE.

A00

PART NO:		
DELTA MODEL: ASB03512HB-F00		
3. MECHANICAL:		
3-1. DIMENSIONS	SEE DIMENSIONS DRAWING	
3-2. FRAME	PLASTIC UL: 94V-0	
3-3. IMPELLER	PLASTIC UL: 94V-0	
3-4. BEARING SYSTEM	SLEEVE BEARING	
3-5. WEIGHT	14.0 (REF.) GRAMS	
4. ENVIRONMENTAL:		
4-1. OPERATING TEMPERATURE	10 TO +70 DEGREE C	
4-2. STORAGE TEMPERATURE	40 TO +75 DEGREE C	
4-3. OPERATING HUMIDITY	5 TO 90 % RH	
4-4. STORAGE HUMIDITY	5 TO 95 % RH	
5. PROTECTION:		
5-1. LOCKED ROTOR PROTECTION		

IMPEDANCE OF MOTOR WINDING PROTECTS MOTOR FROM FIRE IN 96 HOURS OF LOCKED ROTOR CONDITION AT THE RATED VOLTAGE.

5-2. POLARITY PROTECTION

BE CAPABLE OF WITHSTANDING IF REVERSE CONNECTION FOR POSITIVE AND NEGATIVE LEADS.


- 6. RE OZONE DEPLETING SUBSTANCES:
  - 6-1. NO CONTAINING PBBs, PBB0s, CFCs, PBBEs, PBDPEs AND HCFCs.
- 7. PRODUCTION LOCATION
  - 7-1. PRODUCTS WILL BE PRODUCED IN CHINA.

-----

PART NO:

DELTA MODEL: ASB03512HB-F00

8. P & Q CURVE:



\* TEST CONDITION: INPUT VOLTAGE ---- OPERATION VOLTAGE TEMPERATURE ---- ROOM TEMPERATURE HUMIDITY ----- 65%RH

page: 4


PART NO:

DELTA MODEL: ASB03512HB-F00

#### 9. DIMENSION DRAWING:

#### LABEL:





UNIT: mm(INCH)

NOTES: 1. LEAD WIRE: UL 1061 AWG #26
RED WIRE POSITIVE (+)
BLACK WIRE NEGATIVE (-)
BLUE WIRE FREQUENCY (F00)

2. THIS PRODUCT IS ROHS COMPLIANT

-----


PART NO:

DELTA MODEL: ASB03512HB-F00

DELIA MODEL: ASDOSSIZAD-FOO

### 10. FREQUENCY GENERATOR (FG) SIGNAL:

10-1. OUTPUT CIRCUIT - OPEN COLLECTOR MODE:



CAUTION: THE FG SIGNAL LEAD WIRE MUST BE KEPT AWAY FROM "+" LEAD WIRE & "-" LEAD WIRE.

#### 10−2. SPECIFICATION:


 $V_{CE}$  (sat)=0.5V MAX.

 $V_{FG} = 5.0V \text{ TYP. (Vec MAX.)}$ 


 $I_c = 5 \text{mA MAX}.$ 

 $R \ge V_{FG} / I_{C}$ 

### 10−3. FREQUENCY GENERATOR WAVEFORM:



#### FAN RUNNING FOR 4 POLES



N=R.P.M

TS=60/N(SEC)

\*VOLTAGE LEVEL AFTER BLADE LOCKED

\*4 POLES

A00



## **Application Notice**

- 1. Delta will not guarantee the performance of the products if the application condition falls outside the parameters set forth in the specification.
- 2. A written request should be submitted to Delta prior to approval if deviation from this specification is required.
- 3. Please exercise caution when handling fans. Damage may be caused when pressure is applied to the impeller, if the fans are handled by the lead wires, or if the fan was hard-dropped to the production floor.
- 4. Except as pertains to some special designs, there is no guarantee that the products will be free from any such safety problems or failures as caused by the introduction of powder, droplets of water or encroachment of insect into the hub.
- 5. The above-mentioned conditions are representative of some unique examples and viewed as the first point of reference prior to all other information.
- 6. It is very important to establish the correct polarity before connecting the fan to the power source. Positive (+) and Negative (-). Damage may be caused to the fans if connection is with reverse polarity, if there is no foolproof method to protect against such error specifically mentioned in this spec.
- 7. Delta fans without special protection are not suitable where any corrosive fluids are introduced to their environment.
- 8. Please ensure all fans are stored according to the storage temperature limits specified. Do not store fans in a high humidity environment. We highly recommend performance testing is conducted before shipping, if the fans have been stored over 6 months.
- 9. Not all fans are provided with the Lock Rotor Protection feature. If you impair the rotation of the impeller for the fans that do not have this function, the performance of those fans will lead to failure.
- 10. Please be cautious when mounting the fan. Incorrect mounting of fans may cause excess resonance, vibration and subsequent noise.
- 11. It is important to consider safety when testing the fans. A suitable fan guard should be fitted to the fan to guard against any potential for personal injury.
- 12. Except where specifically stated, all tests are carried out at room (ambient) temperature and relative humidity conditions of 25°C, 65% RH. The test value is only for fan performance itself.
- 13. Be certain to connect an "4.7μF or greater" capacitor to the fan externally when the application calls for using multiple fans in parallel, to avoid any unstable power.

Doc. No: FMBG-ES Form 001 Rev. 0001 Date: June 24, 2009