





DESCRIPTION	MATERIAL	FINISH
GROMMET	FLUOROSILICONE RUBBER	COLOR: BLUE
MODULE ASSEMBLY	THERMOSET EPOXY	COLOR: BLACK
CONTACT, SOCKET ASSEMBLY	BERYLLIUM COPPER PER ASTM-B194	GOLD PLATE PER MIL-G-45204
CLIP CONTACT RETAINING	BERYLLIUM COPPER PER ASTM-B194 OR SST PER QQ-S-766	NONE
BRACKET	AL-ALLOY 6061-T4 (.050 THK)	NICKEL PLATE PER MIL-C-26074
CONTACTS	COPPER ALLOY PER MIL-C-32029/1	GOLD PLATE PER MIL-G-45204
SEALING PLUGS	F.E.P. PER MIL-P-19468	COLOR: RED

- 1
- ASSEMBLIES ARE IDENTIFIED WITH "AMP", AMP P/N, DATE CODE, AND DIODE SCHEMATIC ON MODULE AT AREA SHOWN.
- 2
- CONTACTS, INSERTION/EXTRACTION TOOL AND SEALING PLUGS SUPPLIED WITH MODULE ASSEMBLY.
- 3
- MARK ASSEMBLY WITH CUSTOMER PART NO. 12079-20E-012 AT AREA SHOWN.
- 4
- METAL MOUNTING BRACKET NOT BONDED TO MODULE ASSEMBLY.
- 5
- DIODE MAY BE A COMMERCIAL DIODE THAT HAS BEEN SCREENED TO MEET THE REQUIREMENTS OF JANTX1N5552.
- 6
- DIODE MAY BE A COMMERCIAL DIODE THAT HAS BEEN SCREENED TO MEET THE REQUIREMENTS OF JANTX1N5554.

JANTX1N5554			SIZE 20	591858-3
JANTX1N5552			SIZE 20	591858-2
JANTX1N5552		 	SIZE 20	591858-1
DIODE	REMARKS	DESCRIPTION	PART NO	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±	-
1 PLC	±	-
2 PLC	±	-
3 PLC	±	-
4 PLC	±	-
ANGLES	±	-
FINISH	-	

MATERIAL

SEE TABLE

DWN B. LATTUCA 09JAN2006

CHK R. RYAN 08-10-93

APVD R. RYAN 08-10-93

PRODUCT SPEC

APPLICATION SPEC

WEIGHT -

CUSTOMER DRAWING

TE Connectivity

NAME

MODULE, FEED-BACK SIZE 20 ASSEMBLY TJ

SIZE A2

CAGE CODE 00779

DRAWING NO C=591858

RESTRICTED TO -

SCALE 4:1

SHEET 1 of 1

REV E