


LOC	DIST	REVISIONS					
AD	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
			B3	REVISED PER ECO-11-005027	12MAR2011	RK	HMR

1 MATERIAL:
CONTACT: BRASS
LATCH HOUSING, INSERT, COLLET, COLLET NUT:
UL 94V-0 RATED THERMOPLASTIC
COLOR:
COLLET AND INSERT: GRAY
LATCH HOUSING AND NUT: SEE TABLE


2 FINISH:
CONTACT, 0.75µm MIN. GOLD OVER NICKEL

3 SOLDER TERMINATION CONTACT, 28 AWG WIRE MAX.


4. PRODUCT IS SUPPLIED UNASSEMBLED.




SCALE 3:1



INSERT SUB-ASSY
CIRCUIT DESIGNATION VIEW



80° KEYING
SCALE 4:1



0° KEYING
SCALE 4:1

SEE SHEET 2 FOR
PART NUMBER SELECTION

PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN K. MILLER 09MAR2006	TE Connectivity			
		CHK L. BREKOSKY 09MAR2006				
DIMENSIONS:		APVD -	NAME			
mm		PRODUCT SPEC	10 POSITION, CABLE COLLET STRAIGHT PLUG ASSEMBLY 0 AND 80 DEGREE KEYING			
		APPLICATION SPEC				
		114-13184				
MATERIAL		WEIGHT	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
1		-	A2	00779	C-1877848	-
		CUSTOMER DRAWING	SCALE	4:1	SHEET	OF 3
						REV B3

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

LOC

DIST

AD00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

Ø 2.7-Ø 3.9

BLUE

GRAY

80°

7-1877848-2

Ø 4.0-Ø 5.2

BLUE

GRAY

80°

7-1877848-1

Ø 5.3-Ø 6.5

BLUE

GRAY

80°

7-1877848-0

Ø 2.7-Ø 3.9

BLUE

GRAY

0°

6-1877848-9

Ø 4.0-Ø 5.2

BLUE

GRAY

0°

6-1877848-8

Ø 5.3-Ø 6.5

BLUE

GRAY

0°

6-1877848-7

Ø 2.7-Ø 3.9

BLUE

BLACK

80°

6-1877848-6

Ø 4.0-Ø 5.2

BLUE

BLACK

80°

6-1877848-5

Ø 5.3-Ø 6.5

BLUE

BLACK

80°

6-1877848-4

Ø 2.7-Ø 3.9

BLUE

BLACK

0°

6-1877848-3

Ø 4.0-Ø 5.2

BLUE

BLACK

0°

6-1877848-2

Ø 5.3-Ø 6.5

BLUE

BLACK

0°

6-1877848-1

Ø 2.7-Ø 3.9

GREEN

GRAY

80°

6-1877848-0

Ø 4.0-Ø 5.2

GREEN

GRAY

80°

5-1877848-9

Ø 5.3-Ø 6.5

GREEN

GRAY

80°

5-1877848-8

Ø 2.7-Ø 3.9

GREEN

GRAY

0°

5-1877848-7

Ø 4.0-Ø 5.2

GREEN

GRAY

0°

5-1877848-6

Ø 5.3-Ø 6.5

GREEN

GRAY

0°

5-1877848-5

Ø 2.7-Ø 3.9

GREEN

BLACK

80°

5-1877848-4

Ø 4.0-Ø 5.2

GREEN

BLACK

80°

5-1877848-3

Ø 5.3-Ø 6.5

GREEN

BLACK

80°

5-1877848-2

Ø 2.7-Ø 3.9

GREEN

BLACK

0°

5-1877848-1

Ø 4.0-Ø 5.2

GREEN

BLACK

0°

5-1877848-0

Ø 5.3-Ø 6.5

GREEN

BLACK

0°

4-1877848-9

Ø 2.7-Ø 3.9

YELLOW

GRAY

80°

4-1877848-8

Ø 4.0-Ø 5.2

YELLOW

GRAY

80°

4-1877848-7

Ø 5.3-Ø 6.5

YELLOW

GRAY

80°

4-1877848-6

Ø 2.7-Ø 3.9

YELLOW

GRAY

0°

4-1877848-5

Ø 4.0-Ø 5.2

YELLOW

GRAY

0°

4-1877848-4

Ø 5.3-Ø 6.5

YELLOW

GRAY

0°

4-1877848-3

Ø 2.7-Ø 3.9

YELLOW

BLACK

80°

4-1877848-2

Ø 4.0-Ø 5.2

YELLOW

BLACK

80°

4-1877848-1

Ø 5.3-Ø 6.5

YELLOW

BLACK

80°

4-1877848-0

Ø 2.7-Ø 3.9

YELLOW

BLACK

0°

3-1877848-9

Ø 4.0-Ø 5.2

YELLOW

BLACK

0°

3-1877848-8

Ø 5.3-Ø 6.5

YELLOW

BLACK

0°

3-1877848-7

CABLE RANGE

COLLET NUT
COLOR

LATCH HOUSING
COLOR

KEYING

PART NO.

PART NUMBERS 37 THRU 72

Ø 2.7-Ø 3.9

WHITE

GRAY

80°

3-1877848-6

Ø 4.0-Ø 5.2

WHITE

GRAY

80°

3-1877848-5

Ø 5.3-Ø 6.5

WHITE

GRAY

80°

3-1877848-4

Ø 2.7-Ø 3.9

WHITE

GRAY

0°

3-1877848-3

Ø 4.0-Ø 5.2

WHITE

GRAY

0°

3-1877848-2

Ø 5.3-Ø 6.5

WHITE

GRAY

0°

3-1877848-1

Ø 2.7-Ø 3.9

WHITE

BLACK

80°

3-1877848-0

Ø 4.0-Ø 5.2

WHITE

BLACK

80°

2-1877848-9

Ø 5.3-Ø 6.5

WHITE

BLACK

80°

2-1877848-8

Ø 2.7-Ø 3.9

WHITE

BLACK

0°

2-1877848-7

Ø 4.0-Ø 5.2

WHITE

BLACK

0°

2-1877848-6

Ø 5.3-Ø 6.5

WHITE

BLACK

0°

2-1877848-5

Ø 2.7-Ø 3.9

RED

GRAY

80°

2-1877848-4

Ø 4.0-Ø 5.2

RED

GRAY

80°

2-1877848-3

Ø 5.3-Ø 6.5

RED

GRAY

80°

2-1877848-2

Ø 2.7-Ø 3.9

RED

GRAY

0°

2-1877848-1

Ø 4.0-Ø 5.2

RED

GRAY

0°

2-1877848-0

Ø 5.3-Ø 6.5

RED

GRAY

0°

1-1877848-9

Ø 2.7-Ø 3.9

RED

BLACK

80°

1-1877848-8

Ø 4.0-Ø 5.2

RED

BLACK

80°

1-1877848-7

Ø 5.3-Ø 6.5

RED

BLACK

80°

1-1877848-6

Ø 2.7-Ø 3.9

RED

BLACK

0°

1-1877848-5

Ø 4.0-Ø 5.2

RED

BLACK

0°

1-1877848-4

Ø 5.3-Ø 6.5

RED

BLACK

0°

1-1877848-3

Ø 2.7-Ø 3.9

GRAY

GRAY

80°

1-1877848-2

Ø 4.0-Ø 5.2

GRAY

GRAY

80°

1-1877848-1

Ø 5.3-Ø 6.5

GRAY

GRAY

80°

1-1877848-0

Ø 2.7-Ø 3.9

GRAY

GRAY

0°

1877848-9

Ø 4.0-Ø 5.2

GRAY

GRAY

0°

1877848-8

Ø 5.3-Ø 6.5

GRAY

GRAY

0°

1877848-7

Ø 2.7-Ø 3.9

BLACK

BLACK

80°

1877848-6

Ø 4.0-Ø 5.2

BLACK

BLACK

80°

1877848-5

Ø 5.3-Ø 6.5

BLACK

BLACK

80°

1877848-4

Ø 2.7-Ø 3.9

BLACK

BLACK

0°

1877848-3

Ø 4.0-Ø 5.2

BLACK

BLACK

0°

1877848-2

Ø 5.3-Ø 6.5

BLACK

BLACK

0°

1877848-1

CABLE RANGE

COLLET NUT
COLOR

LATCH HOUSING
COLOR


KEYING

PART NO.

PART NUMBERS 1 THRU 36

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm



TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±

1 PLC ±0.13

2 PLC ±0.08

3 PLC ±

4 PLC ±

ANGLES ±1°

FINISH

MATERIAL

-

DWN
K. MILLER
CHK
L. BREKOSKY
APVD
-

09MAR2006
09MAR2006

PRODUCT SPEC
108-2249
APPLICATION SPEC
114-13184
WEIGHT
-

CUSTOMER DRAWING

TE Connectivity

NAME
10 POSITION, CABLE COLLET
STRAIGHT PLUG ASSEMBLY
0 AND 80 DEGREE KEYING

SIZE
A2

CAGE CODE
00779

DRAWING NO
1877848

RESTRICTED TO
-

SCALE
4:1


SHEET
2

OF
3

REV
B3

1471-9 (3/11)

LOC	DIST	REVISIONS					
AD	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
			-	SEE SHEET 1	-	-	-

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 09MAR2006 K. MILLER CHK 09MAR2006 L. BREKOSKY		 TE Connectivity	
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME 10 POSITION, CABLE COLLET STRAIGHT PLUG ASSEMBLY 0 AND 80 DEGREE KEYING	
		0 PLC ±. 1 PLC ±0.13 2 PLC ±0.08 3 PLC ±. 4 PLC ±. ANGLES ±1°		PRODUCT SPEC 108-2249 APPLICATION SPEC 114-13184	
MATERIAL -		FINISH -		SIZE A2	
		WEIGHT -		CAGE CODE 00779	
		CUSTOMER DRAWING		DRAWING NO C-1877848	
				RESTRICTED TO -	
				SCALE 4 : 1	
				SHEET 3 OF 3	
				REV B3	