


2		1					
LOC	DIST	REVISIONS					
E	B	P	LTR	DESCRIPTION	DATE	DWN	APVD
			C 2	REVISED PER ECO-11-005150	29MAR2011	RK	HMR
			N	ECR-16-003725	12MAR2016	KR	TN



- 1 FOR FURTHER INFORMATION SEE DATA SHEET FOR
HS SERIES-ALUMINIUM HOUSED RESISTORS
- 2 FOR A SPECIFIC PN FOR A RESISTANCE VALUE
AND TOLERANCE, PLEASE REFER TO DMF
- 3 TECHNICAL SPECIFICATION

DISSIPATION AT 25°C : 25 WATTS MOUNTED
ON STANDARD HEATSINK

BS OHMIC RANGE : R051 TO 27K




STABILITY : $\Delta R < = 1\%$ PER 1000hrs

ISOLATION VOLTAGE : 2500V DC/AC pk

MAX WORKING VOLTAGE : 500V DC/AC rms

TEMP COEFFICIENT : > 1R0 50ppm
> 100R 25ppm

CLIMATIC CATEGORY : 55/200/56



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	29.SEP.05	TE Connectivity		
		CHK	30.SEP.05			
		J CATCHPOLE	30.SEP.05	NAME HSA25 METAL CLAD RESISTOR		
		APVD	30.SEP.05			
		J CATCHPOLE		SIZE A3		
		PRODUCT SPEC				
		-		CAGE CODE 00779		
		APPLICATION SPEC				
		-		DRAWING NO C-1625971		
		WEIGHT	-			
		-		RESTRICTED TO -		
		CUSTOMER DRAWING				
		SCALE	3:1	SHEET 1 OF 1		
		REV	N			