



### Main

Range of product	9007
Series name	Heavy duty
Device short name	C
Head type	Plunger head
Type of operator	Spring return Spring return roller plunger
Switch actuation	Horizontal
Contacts type and composition	1 NO/1 NC
Contact operation	Snap action
Operating distance	0.25 inch
Operating travel	0.08 in 0.02 in

### Complementary

Body material	Zinc alloy
Switch function	SPDT-DB
Contact form	Form Z
Contacts material	Silver alloy (Ag/Ni)
Minimum force for tripping	3 lbf
[Ie] rated operational current	10 A, Q600 10 A, A600
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	<= 600 V
Local signalling	1 LED (load energised)
Product certifications	CE CSA UL listed
Provided equipment	Receptacle

### Environment

ambient air temperature for operation	0...185 °F
---------------------------------------	------------

### Offer Sustainability

Not Green Premium product	Not Green Premium product
Will not be Compliant	Will not be Compliant
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>	For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>

### Contractual warranty

Warranty period	18 months
-----------------	-----------