


REVISIONS			
LTR	DESCRIPTION	DATE	APPROVED
B	REVISED PER ECN# T-21394	4/10/97	Z. TEMAN
C	REVISED PER ECN# T-21730	9/19/97	Z. TEMAN



- NOTE:
THIS DUST CAP IS TO BE USED ON A 5/16-32 THREADED INTERFACE CONNECTOR.
- 1.0 MATERIALS AND FINISHES
- 1.1 DUST CAP COUPLING NUT: BRASS ALLOY 360, HALF HARD PER ASTM B 16.
TIN PLATED PER MIL-T-10727, OVER NICKEL PER QQ-N-290.
- 1.2 INTERFACIAL SEAL: SILICONE RUBBER
- 1.3 SCREW AND LANYARD: STAINLESS STEEL, PASSIVATED PER QQ-P-35.

If this document is printed it becomes uncontrolled.
Check for the latest revision.

SPECIFICATION CONTROL DRAWING

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. METRIC DIMENSIONS ARE IN BRACKETS. DECIMALS .XXX ± — [— mm] .XX ± — [— mm] ANGLES .X ± — WEIGHT — lbs [— g]	DRAWN	ZET	2/20/97	tyco Electronics		Tyco Electronics Corporation 300 Constitution Drive Menlo Park, CA. 94025 U.S.A.		Raychem	
	CHECKED			TITLE DUST CAP, THREADED, COUPLED,					
	APPROVED								
	APPROVED	P.DUTTON							
	CAD NAME			T21730					
THIRD ANGLE PROJECTION					SIZE A	CODE IDENT. NO. 06090	DWG. NO. D-600-0083		REV C
DO NOT SCALE THIS DRAWING								SHEET 1 OF 1	