








THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
D	LE315A0035~37	2015/09/19	Joyy	Update The Drawing
E	C180139	2018/11/27	Mafei	Remove The Shrink Tube.
F	C191730	2019/10/07	Vicky	Update Code & Wire Tolerance



Note:
* $\varnothing$ Important Dimension To Check.
* Waterproof Rate: IP67
* Housing: M-PPE, Black.
* Female Pin: Copper Alloy, Gold Plated.
* Gasket: Silicone, Gray.
* Wire Harness: UL1015 16#
* Blind holes for the screws used M3X0.5mm
* Blind Hole Size M3X0.5mm
* Screw Torque: 1.5~2kgf.cm
* Wire harness Tolerance: 100 ± 10mm
101~300 ± 15mm
301~1000 ± 20mm
* Prohibiting the use of place in oils

UNIT:mm	TOLERANCE	TITLE	SCALE	SIZE	SHEET	OF
±0.5mm		MIDDLE PANEL RBL F CONN F PIN	1:1	A4	1	2
		REV. F	WC-REV. A.14	$\varnothing$ Inspection item		

ITEM NO	DWG NO	CUSTOMER	DRAWN BY	CHECKED BY	APPROVED BY	DATE
	CB-XXRFFC-RSTAXX	ALTW	Mafei	Jerry	Max	2018-11-27
						2018-11-27
						2018-11-27



CB-XXRFFC-RS7AXX

Middle Size Current Rating 10A

XX:No. Of Pin(Pin 數)

R:Panel Rear Mounting(後鎖嵌面板式)

F:Female Connector(母座)

F:Female Pin(母Pin)

C:CrimpType(夾線組裝式)

10 :100mm
15 :150mm
20 :200mm
f
A0 :1000mm

△A0 :1000mm

Cable Pitch Unit:50mm


Wire Length(L):100~1000mm




A: UL 1015

7:IP67(防水等級 67)

S:Square(方座)

R:Snap in With Latch(彈臂卡合式)



Pin Out	4 -- 3 Red 紅 2 -- 1 Black 黑	4 Green 綠 3 Red 紅 2 -- 1 Black 黑	4 Orange 橙 3 Red 紅 2 Brown 棕 1 Black 黑
Pin Assignments Front View	 2Pin	 3Pin	 4Pin

UNIT:mm		TITLE MIDDLE PANEL RBL F CONN F PIN	
TOLERANCE		SCALE 1:1	SIZE A4
±0.5mm		SHEET 2	OF 2
REV. F	WC-REV. A.14	QC:Inspection item	

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY Mafei	DATE 2018-11-27
DWG NO CB-XXRFFC-RS7AXX	CHECKED BY Jerry	DATE 2018-11-27
CUSTOMER ALTW	APPROVED BY Max	DATE 2018-11-27