

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT PART NO.	MINIMUM LENGTH	WEIGHT	FERRULE TYPE
F9D4-4M1	39.37 in. [1 meter]	.70 lb./10 pcs. [318.4g/10 pcs.]	ZIRCONIA
F9D4-4M2	78.74 in. [2 meters]	1.01 lb./10 pcs. [460.8g/10 pcs.]	ZIRCONIA
F9D4-4M3	118.11 in. [3 meters]	1.32 lb./10 pcs. [603.2g/10 pcs.]	ZIRCONIA
F9D4-4M6	236.2 in. [6 meters]	2.26 lb./10 pcs. [1030.4g/10 pcs.]	ZIRCONIA
F9D4-4M9	354.3 in. [9 meters]	3.20 lb./10 pcs. [1457.6g/10 pcs.]	ZIRCONIA
F9D4-4M10	393.7 in. [10 meters]	3.52 lb./10 pcs. [1600.0g/10 pcs.]	ZIRCONIA
F9D4-4M12	472.4 in. [12 meters]	4.14 lb./10 pcs. [1884.8g/10 pcs.]	ZIRCONIA
F9D4-4M15	590.5 in. [15 meters]	5.08 lb./10 pcs. [2312.0g/10 pcs.]	ZIRCONIA

3mm YELLOW JACKETED
RISER RATED DUPLEX
FIBER OPTIC CABLE

PRINTED
CABLE

BLUE
BOOTS

DUST CAPS

SINGLEMODE
FC CONNECTORS

NOTES:

1. SEE CURRENT CATALOG FOR PACKAGE QUANTITY.
2. DUPLEX 3mm JACKETED SINGLEMODE, 9/125 μ m GLASS OPTICAL FIBER, RISER RATED.
3. TERMINATED WITH FC CONNECTORS. ASSEMBLED WITH TEMPERATURE CURED EPOXY.
4. CABLE JACKET COLOR IS YELLOW. BOOT COLOR IS BLUE.
5. MINIMUM INSERTION LOSS PER CONNECTOR: .35dB PER FOTP-171.
6. MINIMUM RETURN LOSS PER CONNECTOR: 40dB OR GREATER FOR SPC POLISH.
7. DUST CAPS MAY VARY FROM ONES SHOWN.
8. ALL DIMENSIONS IN BRACKETS ARE METRIC.

CAD FILENAME/LAYERS

M01010CN_DC_00A.PRT

PANDUIT

CORP. TINLEY PARK, ILLINOIS

DUPLEX SINGLEMODE FIBER OPTIC PATCHCORDS
FC TO FC CONFIGURATION
(F9D4-4M SERIES) CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:

(.X) $\pm$ (.XXX) $\pm$
(.XX) $\pm$ ANGLES $\pm$

UNLESS OTHERWISE SPECIFIED,

ALL DIMENSIONS ARE GIVEN
IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY
EFK

MAT'L:

SCALE
NONE

DATE
01-14-01

SEE NOTES

DRAWING NO.

01010-38

DWG
A
SIZE

R 01-14-01 EFK RELEASED FOR PRODUCTION

01010-38

REV DATE BY CHK DESCRIPTION

ECN - R CUST SUP OTH