


DETAIL Z
SCALE 8:1

NOTES:

1. MATERIAL: HOUSING: NYLON, UL94V-2, IEC 60335-1 5TH EDITION GLOW WIRE CAPABLE, COLOR: BLACK
PINS: BRASS
2. FINISH: (197) = OVERALL REFLOWED MATTE TIN: 0.00152/.000060 MIN, OVER 0.00127/.000050 MIN, NICKEL OVERALL.
(208) = SELECT GOLD: 0.00038/.000015 MIN, SELECT MATTE TIN: 0.00254/.000100 MIN, BOTH OVER 0.00127/.000050 MIN NICKEL.
(228) = SELECT GOLD: 0.00076/.000030 MIN, SELECT MATTE TIN: 0.00254/.000100 MIN, BOTH OVER 0.00127/.000050 MIN NICKEL.
3. PRODUCT SPECIFICATION: PS-171813-0001, PS-171813-0002
4. PACKAGING INFORMATION: SEE CHART
5. SOLDERABILITY: PER SMES-152.
6. PIN PUSH-OUT FORCE: PRIOR TO SOLDERING, A 3 LB. MINIMUM FORCE IN EITHER DIRECTION
7. PARTS ARE STACKABLE END TO END ON 3.96/.156 CENTERS.
8. THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002.
9. SLOTS ON BACKWALL ARE BETWEEN CIRCUITS. SEE CHART FOR LOCATION.
10. CIRCUIT 1 DESIGNATION IS USED TO DEFINE VOID LOCATION. CIRCUIT 1 MAY OR MAY NOT LINE UP WITH CIRCUIT 1 ON THE MATING HOUSING.
11. FEATURE MAY OR MAY NOT EXTEND ACROSS THE ENTIRE FACE OF THE PART. SEE DETAIL Z.

FEATURE MAY BE ON EITHER
SIDE OF THE PART

SEE NOTE 11
AND DETAIL Z

11.33±0.51
.446±0.020

2.41
.095
REF

-E-

5.11
.201
AT DATUM -D-

GOLD

M

3.30
.130
REF

Y

±0.25
±0.10
TYP

TIN

10.01±0.51
.394±0.020

P
REF.

CENTERLINE OF PIN AT TIP
NOT TO VARY FROM CENTERLINE OF
PIN AT DATUM -E- BY MORE THAN
0.20 / .008 IN ANY DIRECTION.

CENTERLINE OF PIN AT TIP
NOT TO VARY FROM CENTERLINE OF
PIN AT DATUM -D- BY MORE THAN
0.20 / .008 IN ANY DIRECTION.

SEE DETAIL Z
SEE NOTE 11

OPTIONAL VOIDED CIRCUIT
SEE CHART FOR LOCATIONS

CIRCUIT 1
SEE NOTE 10

SEE NOTE 9

1.91
.075
AT -D-


DIM. A REF.

DIM. B

3.96
.156
REF.

TYP. BETWEEN ANY
2 CONSECUTIVE
CIRCUITS AT DATUM -D-

3.96±0.05
.156±0.002
TYP
NON-ACCUMULATIVE



PCB LAYOUT: COMPONENT SIDE

1.73±0.05
.068±0.002
DIA TYP

CIRCUIT SIZE	DIM. A	DIM. B	SLOT LOCATION BETWEEN CIRCUITS
2	7.77 .306	3.96±0.05 .156±0.002	NONE
3	11.73 .462	7.92±0.10 .312±0.004	NONE
4	15.70 .618	11.89±0.15 .468±0.006	NONE
5	19.66 .774	15.85±0.15 .624±0.006	NONE
6	23.62 .930	19.81±0.18 .780±0.007	3 & 4
7	27.58 1.086	23.77±0.18 .936±0.007	4 & 5
8	31.55 1.242	27.74±0.20 1.092±0.008	4 & 5
9	35.51 1.398	31.70±0.20 1.248±0.008	5 & 6
10	39.47 1.554	35.66±0.23 1.404±0.009	5 & 6
11	43.43 1.710	39.62±0.23 1.560±0.009	6 & 7
12	47.40 1.866	43.59±0.25 1.716±0.010	4 & 5 8 & 9

ADD 171814-9999 EC NO: UCP2014-5400 DRWN:MKIPPER 2014/06/24 CHKD:JBELL 2014/06/24 APPR:FSMITH 2014/06/27	DESCRIPTION	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)			DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION					
						MM/IN		4:1	INCH						
			 		mm	INCH	DRAWN BY	DATE	TITLE KK RPC .156 HEADER ASS'Y FRICTION LOCK RIGHT ANGLE W/O PEGS molex						
				4 PLACES	± ---	± ---	MKIPPER	2012/09/14							
				3 PLACES	± ---	± .010	CHECKED BY	DATE							
				2 PLACES	± 0.25	± .015	SSOUSEK	2012/09/14							
				1 PLACE	± 0.38	± ---	APPROVED BY	DATE							
				0 PLACE	±	±	FSMITH	2013/06/11	DOCUMENT NO. SD-171814-0001						
			ANGULAR ±1/2°			MATERIAL NO.		SHEET NO. 1 OF *							
			DRAFT WHERE APPLICABLE			SEE CHART									
A3	REV		MUST REMAIN WITHIN DIMENSIONS			SIZE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION								

OPTIONS	Group	171814-0002/0012	Group	171814-1002/1012	Group	171814-2002/2012
	Plating:	197 – TIN	Plating:	208 – 15 GOLD	Plating:	228 – 30 GOLD
	Mating M	11.33 / .446	Mating M	11.33 / .446	Mating M	11.33 / .446
	Gold Loc G	N/A	Gold Loc G	6.85 / .270	Gold Loc G	6.85 / .270
	Height Y	5.41 / .213	Height Y	5.41 / .213	Height Y	5.41 / .213
	PC Tail P	2.54/ .100	PC Tail P	2.54/ .100	PC Tail P	2.54/ .100
	Tin Loc T	OVERALL	Tin Loc T	5.08 / .200	Tin Loc T	5.08 / .200
	Voided Ckts	NONE	Voided Ckts	NONE	Voided Ckts	NONE
	Pack Per	PK-41792-002 BULK	Pack Per	PK-41792-002 BULK	Pack Per	PK-41792-002 BULK
Ckts	Material No		Material No		Material No	
2	171814-0002		171814-1002		171814-2002	
3	171814-0003		171814-1003		171814-2003	
4	171814-0004		171814-1004		171814-2004	
5	171814-0005		171814-1005		171814-2005	
6	171814-0006		171814-1006		171814-2006	
7	171814-0007		171814-1007		171814-2007	
8	171814-0008		171814-1008		171814-2008	
9	171814-0009		171814-1009		171814-2009	
10	171814-0010		171814-1010		171814-2010	
11	171814-0011		171814-1011		171814-2011	
12	171814-0012		171814-1012		171814-2012	

REV:	<u>ECR/ECN INFORMATION:</u>	<u>TITLE:</u>			<u>SHEET No.</u>
A3	<u>EC No.:</u> UCP2014-5400	KK RPC 156 HEADER ASSEMBLY FRICTION LOCK RIGHT ANGLE W/O PEGS			- 2 -
	<u>DATE:</u> 7/8/2014				
<u>DOCUMENT NUMBER:</u> SD-171814-0001		<u>CREATED / REVISED BY:</u> MKIPPER	<u>CHECKED BY:</u> JBELL	<u>APPROVED BY:</u> FSMITH-ROEMER	

OPTIONS	Group	171814-0102/0112	Group		Group	
	Plating:	197 – TIN	Plating:		Plating:	
	Mating M	11.43 / .450	Mating M		Mating M	
	Gold Loc G	N/A	Gold Loc G		Gold Loc G	
	Height Y	5.41 / .213	Height Y		Height Y	
	PC Tail P	3.96/ .156	PC Tail P		PC Tail P	
	Tin Loc T	OVERALL	Tin Loc T		Tin Loc T	
	Voided Ckts	NONE	Voided Ckts		Voided Ckts	
	Pack Per	PK-41792-002 BULK	Pack Per		Pack Per	
Ckts	Material No		Material No		Material No	
2	171814-0102					
3	171814-0103					
4	171814-0104					
5	171814-0105					
6	171814-0106					
7	171814-0107					
8	171814-0108					
9	171814-0109					
10	171814-0110					
11	171814-0111					
12	171814-0112					

REV:	ECR/ECN INFORMATION:	TITLE:	SHEET No.
A3	EC No.: UCP2014-5400	KK RPC 156 HEADER ASSEMBLY	- 3 -
	DATE: 7/8/2014	FRICTION LOCK	
		RIGHT ANGLE W/O PEGS	
DOCUMENT NUMBER:	CREATED / REVISED BY:	CHECKED BY:	APPROVED BY:
SD-171814-0001	MKIPPER	JBELL	FSMITH-ROEMER

OPTIONS	Group	171814-3002/3012	Group	171814-4002/4012	Group	
	Plating:	197 – TIN	Plating:	208 – 15 GOLD	Plating:	
	Mating M	11.33 / .446	Mating M	11.33 / .446	Mating M	
	Gold Loc G	N/A	Gold Loc G	6.85 / .270	Gold Loc G	
	Height Y	5.41 / .213	Height Y	5.41 / .213	Height Y	
	PC Tail P	2.54/ .100	PC Tail P	2.54/ .100	PC Tail P	
	Tin Loc T	OVERALL	Tin Loc T	5.08 / .200	Tin Loc T	
	Voided Ckts	NONE	Voided Ckts	NONE	Voided Ckts	
	Pack Per	PK-171814-0001 TAPE AND REEL	Pack Per	PK-171814-0001 TAPE AND REEL	Pack Per	
Ckts	Material No		Material No		Material No	
2	171814-3002		171814-4002			
3	171814-3003		171814-4003			
4	171814-3004		171814-4004			
5	171814-3005		171814-4005			
6	171814-3006		171814-4006			
7	171814-3007		171814-4007			
8	171814-3008		171814-4008			
9	171814-3009		171814-4009			
10	171814-3010		171814-4010			
11	171814-3011		171814-4011			
12	171814-3012		171814-4012			

REV:	ECR/ECN INFORMATION:	TITLE:	SHEET No.
A3	EC No.: UCP2014-5400	KK RPC 156 HEADER ASSEMBLY FRICTION LOCK RIGHT ANGLE W/O PEGS	- 4 -
	DATE: 7/8/2014		
DOCUMENT NUMBER:	CREATED / REVISED BY:	CHECKED BY:	APPROVED BY:
SD-171814-0001	MKIPPER	JBELL	FSMITH-ROEMER

OPTIONS	Group	171814-9999	Group		Group	
	Plating:	197 – TIN	Plating:		Plating:	
	Mating M	11.43 / .450	Mating M		Mating M	
	Gold Loc G	N/A	Gold Loc G		Gold Loc G	
	Height Y	5.41 / .213	Height Y		Height Y	
	PC Tail P	3.96/ .156	PC Tail P		PC Tail P	
	Tin Loc T	OVERALL	Tin Loc T		Tin Loc T	
	Voided Ckts	3, 5, 7	Voided Ckts		Voided Ckts	
	Pack Per	PK-41792-002 BULK	Pack Per		Pack Per	
Ckts	Material No		Material No		Material No	
2						
3						
4						
5						
6						
7	171814-9999					
8						
9						
10						
11						
12						

REV:	ECR/ECN INFORMATION:	TITLE:	SHEET No.
A3	EC No.: UCP2014-5400	KK RPC 156 HEADER ASSEMBLY	- 5 -
	DATE: 7/8/2014	FRICTION LOCK	
		RIGHT ANGLE W/O PEGS	
DOCUMENT NUMBER:	CREATED / REVISED BY:	CHECKED BY:	APPROVED BY:
SD-171814-0001	MKIPPER	JBELL	FSMITH-ROEMER