





RU8-160-25-SE-L-DV-BL



HSC8-050-02-19-DP

(0.80 mm) .0315"

RU8, HSC8 SERIES

HIGH-SPEED RISER CARD KIT

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?RU8

CONNECTOR

Insulator Material:

Black LCP

Contact:

BeCu

Plating:

Au or Sn over 50 μm (1.27 μm) Ni

Current Rating:

3.1 A per pin (6 adjacent pins powered)

Operating Temp:

-55 °C to +125 °C

EDGE RATE
CONTACT

RU8 1 POSITIONS PER ROW

STACK HEIGHT

SIGNAL ROUTING

PLATING OPTION

DV

BL

OTHER OPTION

40, 50, 60

Kit contains two connectors and one card. Assembly required.

-19
= (19 mm) .748"

-25
= (25 mm) .984"

-30
= (30 mm) 1.180"

-SE
= Single-Ended

-DP
= Differential Pair

-L
= 10 μm (0.25 μm) Gold on contact, Matte Tin on tail (Plating for connectors) Plating for Card is Hard Gold

-BL
= Board Locks (Bottom Socket only) (Not available on -19 stack height)

Leave blank for Trays

-K
= (5.50 mm) .217" DIA Polyimide Film Pick & Place Pad

-TR
= Tape & Reel

Note:
Other Gold plating options available.

PROCESSING

Lead-Free Solderable:

Yes

SMT Lead Coplanarity:

(0.10 mm) .004" max (40-60)

RoHS Compliant:


Yes

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



Note: While optimized for 50 Ω applications, this connector with alternative signal/ground patterns may also perform well in certain 75 Ω applications.



NO. OF POSITIONS PER SIDE	A	B	-SE TOTAL SIGNAL LINES	-DP TOTAL SIGNAL PAIRS
40	(39.80) 1.567	(51.05) 2.010	40	26
50	(47.80) 1.882	(59.05) 2.325	50	32
60	(55.80) 2.197	(67.05) 2.640	60	38

Note: Some lengths, styles and options are non-standard, non-returnable.

Mates with:
HSEC8

SPECIFICATIONS

For complete specifications see www.samtec.com?HSC8

Conductor:

1/2 oz Copper

Contact Area:

Hard Gold Plated

Insulator:

FR-4

RoHS Compliant:

Yes

HSC8

NUMBER OF POSITIONS PER SIDE

CARD STYLE

STACK HEIGHT

SIGNAL ROUTING

-040, -050, -060

-02
= (1.60 mm) .062" thick card

-19
= (19 mm) .748"


-25
= (25 mm) .984"

-30
= (30 mm) 1.180"

-SE
= Single-Ended

-DP
= Differential Pair

NO. OF POSITIONS PER SIDE	-SE TOTAL SIGNAL LINES	-DP TOTAL SIGNAL PAIRS
-40	40	26
-50	50	32
-60	60	38



STACK HEIGHT	A
-19	(14.84) .584
-25	(20.84) .820
-30	(25.84) 1.017

Note:
Some sizes, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications.

Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.