Product datasheet Characteristics

9001KZC194



Main

Range of product	Harmony 9001K
Product or component type	Security control station
Device short name	9001KZC
Lock type	Lock cylinder, 7 tumbler pins

Complementary

oompicilicituity	
Size	30 mm
Enclosure/cubicle description	Flush mounting
Enclosure material	Stainless steel
Type of installation	Indoor
Control station composition	1 key selector switch with spring return operator, OPEN-CLOSE marking
Type of keylock	Best
Key withdrawal position	Center
Connections - terminals	Screw clamp terminal
[Ue] rated operational voltage	300 V
[le] rated operational current AC	15 A
Product weight	3.75 lb(US) (1.7 kg)

Environment

NEMA degree of protection	NEMA 1
environmental characteristic	Waterproof
product certifications	CE CSA UL listed
ambient air temperature for operation	-13140 °F (-2560 °C)
ambient air temperature for storage	-40158 °F (-4070 °C)
ambient air temperature for storage	-40158 °F (-4070 °C)

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0627 - Schneider Electric declaration of conformity	Compliant - since 0627 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Nickel compounds, which is known to the State of California to cause cancer, and	Nickel compounds, which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	eDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period

18 months

