



Technical drawing of the top view of a 15-pin D-sub connector. The drawing shows a rectangular body with a central 15-pin female connector. The pins are arranged in two rows: 7 pins on the top and 8 pins on the bottom. The pins are numbered 1 through 15 from left to right. The drawing includes mounting holes and a central hole. A dimension line indicates a distance of 0.250,4 PL with a tolerance of $\pm 0,15$.

- 1 PLATED GOLD .000050 THK. FOR A LENGTH OF .343 IN.
FROM MATING END OF CONTACT WITH POINT OF MEASUREMENT
.150±.025 FROM MATING END OF CONTACT; REMAINDER
PLATED TIN—LEAD .000100 TO .00030 THK, ALL OVER
NICKEL .000050 THK.
- 2 MOUNTING LATCHES FOR PLUG MODULES AND
(OPTIONAL) PIN FIELD DUST COVER.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 5-12-87 TERESA K. BLACK CHK 10-16-87 K. AYER APD 10-16-87 K. AYER		 Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME	
INCHES		0 PLC ± 1 PLC ± 2 PLC ± 4 PLC ± .010 4 PLC ± ±		ASSEMBLY, RECEPTACLE, P.C.B. VERSION, 75 POSITION, WIRE INTEGRATION CONNECTOR	
		PRODUCT SPEC — APPLICATION SPEC —		SIZE A1	
MATERIAL		FINISH		CAGE CODE	
SEE CALL OUT		SEE CALL OUT		DRAWING NO	
		WEIGHT		00779  213463	
		CUSTOMER DRAWING		SCALE 2:1 SHEET 1 of 1 REV	