HUBER+SUHNER® DATA SHEET Type: Sucotest Assemblies



Description

ID (Product Code) 84002061

Description (Product) ST18/SMAm/SMAm/36in

Product Configuration

 Cable
 SUCOTEST_18

 Connector A
 SF_11_SMA-373

 Connector B
 SF_11_SMA-373

Connector A Connector B

Technical Data

Electrical Data

Impedance 50 Ω

Operating Frequency 6 GHz to 18 GHz

Min. Return Loss ≥ 25 dB Max. Attenuation 1.51 dB

Max. Power Handling 131 W @ 18 GHz Signal Delay 4.3 ns ± ns

Max. Operating Voltage
Min. Screen Effectiveness
2.5 kV_{rms} (at sea level)
- 90 dB up to 18 GHz

Mechanical Data

Length REF/REF 914 mm
Min. Bending Radius repeated 100 mm
Max. Tensile Force 200 N
Weight 0.68 kg

Environmental Data

Operating Temperature -55 °C... + 105 °C

2002/95/EC, RoHS compliant

2002/96/EC, WEEE no special marking needed

Related Documents

Outline Drawing Assembly
Data Sheet Cable
Data Sheet Connector A
Data Sheet Connector B
DOC-0000332304
Data Sheet Connector B
DOC-0000332304

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG RF Technology 9100 Herisau, Switzerland Phone +41 (0)71 353 41 11

Phone +41 (0)/1 353 41 11 Fax +41 (0)/1 353 45 90 www.hubersuhner.com

Document: DOC-0000332055 J Issued: 15.09.10 Uncontrolled Copy Page 1/1