NOTES:

1. ROHS COMPLIANT
2. MATERIAL:
   - PANEL CONNECTOR - THERMOPLASTIC, WHITE, UL RATING 94-V0
   - HEADER CONNECTOR - POLYESTER, UL RATING 94-V0
   - LENS - POLYCARBONATE - UL RATING 94-V2
   - MOISTURE SEAL - EPDM
   - LOCK WASHER - STEEL, NICKEL PLATE
   - TERMINALS - PHOSPHER BRONZE, TIN PLATE
   - WIRE - 24 AWG 1007/1569
3. MOUNTING: HOLE SIZE .313" (7.9mm) OPENING ON 1/2" CENTERS (12.7mm)
4. PANEL THICKNESS: UP TO .125" (3.18mm) MAX
5. LED LEAD LENGTH: .250" +/- .01 (6.35mm +/- .254)
6. FOR STANDARD DRY APPLICATIONS USE CMC 441, FOR WET OR DRY APPLICATIONS USE CMS 442 (MEETS NEMA 6P/ IP67)
7. LABEL TEXT: "CNX 410 XXX; XXX0 Ohms"
8. U.S AND FOREIGN PATENT ISSUED

REVISIONS					
ECN #	REV.	DESCRIPTION	DATE	INITIALS	CHK'D
425	000	REVISED PER ECR 032112ED01	5/1/12	KH	ED

LED (ORDER SEPARATELY)



5MM LED

CABLE ORDERING CODE EXAMPLE:

CNX 410 056 E02 4 1 08

* CALL FACTORY FOR ADDITIONAL OPTIONS

RESISTOR *	
012 =	120 OHMS
018 =	180 OHMS
033 =	330 OHMS
056 =	560 OHMS
120 =	1200 OHMS
220 =	2200 OHMS

TERMINATION *	
X =	STRIPPED END
E =	SINGLE ROW LOCKING HEADER

WIRE SIZE *	
4 =	24 AWG

WIRE COLOR *	
1 =	WHITE - BLACK
2 =	RED - BLACK

WIRE LENGTH *	
04 =	4 INCHES (101.6mm)
06 =	6 INCHES (152.4mm)
08 =	8 INCHES (203.2mm)
12 =	12 INCHES (304.8mm)
18 =	18 INCHES (457.2mm)
24 =	24 INCHES (609.6mm)



LENS W/ LOCKWASHER (ORDER SEPARATELY)



CMC 441



CMS 442 (MOISTURE SEALED)

DIMENSION STYLE: INCHES / MM
GENERAL TOLERANCES UNLESS OTHERWISE SPECIFIED:
INCHES ±.500
MM ±12.7

THIRD ANGLE PROJECTION

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VISUAL COMMUNICATIONS COMPANY, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VISUAL COMMUNICATIONS COMPANY, INC IS PROHIBITED.

APPROVAL		DATE
DRAWN	KHOWARD	5/1/12
CHECKED	EDEGUZMAN	5/2/12

MATERIAL: SEE NOTES

FINISH: N/A

DO NOT SCALE DRAWING

12780 DANIELSON CT, SUITE A, POWAY, CA 92064 U.S.A
PHONE: (800) 522-5546 EMAIL: vccsales@vcclite.com

TITLE: CNX 410 CABLE ASSEMBLY

SIZE	DWG. NO.	REV
B	CNX 410 XXX ASSY	000

SCALE: 2:1 | SHEET 1 OF 1