

This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary

2 W

DC- 8 GHz


SMB

COAXIAL ATTENUATOR

issue
15. jul. 93

Page
1 / 1

DRAWING



General tolerances: ± 0.5 mm

R F CHARACTERISTICS

FREQUENCY RANGE : DC - 8 GHz
IMPEDANCE : 50 Ohms
ATTENUATION - NOMINAL : 20 dB

FREQUENCY	DC- 4 GHz	4 - 8 GHz
V.S.W.R	≤ 1.15	≤ 1.30
DEVIATION (dB)	+ 0.5 / - 0.5	+ 0.5 / - 0.5

TEMPERATURE SENSITIVITY : $4 \times 10^{-4} \frac{\text{dB}}{\text{dB} \times ^\circ\text{C}}$


PEAK POWER at 25°C (1 μ s, 1%.) : 100 W
AVERAGE POWER at 25°C : 2 W

MECHANICAL CHARACTERISTICS

CONNECTORS : SMB male/female per MIL-C 39012
WEIGHT : < 5 g

ENVIRONMENTAL CHARACTERISTICS

OPERATING TEMPERATURE RANGE (°C) : -55 , +125
STORAGE TEMPERATURE RANGE (°C) : -55 , +125



QUALITY
Dpt app. _____

CREATION

PEN : CAT

EP : _____

Nom : KL

Date: 24. apr. 89

15. jul. 93

New issue

ISSUE

REVISIONS

NAME

HS

RADIALl®

101. Philibert Hoffmann
- Z.I Ouest -
93116 ROSNY/BOIS Cedex-FRANCE
Phone: 33.1.49353535
Fax : 33.1.48546363
Tlx RADIA 235220F