


| Manufacturer | MaxStream, Inc. | | |
|-------------------------------|---|---------------|---------------|
| Part Number | A09-F2NF-M | A09-F5NF-M | A09-F8NF-M |
| Photo |  | | |
| Specific Freq. (MHz) | 915 | | |
| Gain | 2.1dBi (0dBd) | 5.1dBi (3dBd) | 8.1dBi (6dBd) |
| Maximum Power Input (Watts) | 100 | | |
| Product Narrative | Base station Antenna. Heavy wall, gold anodized 1 1/4" aluminum mounting sleeve Precision copper clad elements sealed in white ultraviolet-inhibiting fiberglass radome for weatherability. | | |
| Type | Fiberglass Omni-directional 900 MHz | | |
| General Freq. (MHz) | 902-928 | | |
| Bandwidth @ Rated VSWR (MHz) | 26 | | |
| VSWR | 1.5:1 | | |
| Impedance | 50 ohms | | |
| Horizontal Beam Width | 360 Deg. | | |
| Vertical Beam Width | 75 Deg. | 33 Deg. | 17 Deg. |
| Polarization | Vertical | | |
| Lightning Prot. | DC Ground | | |
| Size (HxWxD") | 15" | 25" | 65" |
| Weight (lbs) | 0.7 | 1.0 | 4.0 |
| Rated Wind Velocity (MPH) | 125 | | |
| Wind Load, (sq ft) | Not Specified | | |
| Lateral Thrust @ RWV | Not Specified | | |
| Bending Moment @ RWV (ft lbs) | Not Specified | | |
| Connector (direct) | Recessed type "N" female connector | | |
| Jumper Included | None | | |
| Connector Placement | Bottom | | |
| Mount Hdw. Incl. | 2 Extruded Aluminum brackets | | |
| Incl. Hardware Fits | Up to 2-1/2" pipe | | |
| Warranty | 1 Year | | |
| Qty/Uom | 1 EACH | | |