




THIS DRAWING IS UNPUBLISHED.	RELEASED FOR PUBLICATION	20
(C) COPYRIGHT 20 BY - ALL RIGHTS RESERVED.		

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	4	REVISED TO SHOW ALL WIRES	020CT2015	JS	CG
	5	NOTE CLARIFICATION	03NOV2015	MM	MM
	6	REVISED TO SHOW PART CHANGES	29DEC2015	JS	CG



SEE SHEET 2 FOR
WIRING COLOR CODE



NOTES:

1. MATERIALS:
HOUSINGS: GLASS-FILLED THERMOPLASTIC, UL 94V-0 RATED
SIGNAL CONTACTS (2 OR 4) AND LINE VOLTAGE CONTACTS (3):
COPPER ALLOY

2. FINISH:
SIGNAL CONTACTS (2 OR 4): NICKEL UNDERPLATE ENTIRE
CONTACT 0.127 μ m MIN THICK. GOLD PLATE CONTACT
PAD AREA (MATING FACE SIDE ONLY) 0.76 μ m MIN THICK.
MATTE TIN PLATE TAB ON BOTH SIDES 0.30 μ m MIN THICK.
LINE VOLTAGE CONTACTS (3): TIN PLATE.

3 LINE VOLTAGE CONDUCTORS (3):
14 AWG, 600V, 150°C RATED, COPPER 41/30 STRANDED
PER UL STYLE AWM 3321.

4 MATING INTERFACE PER ANSI C136.41-2013.

5 OPTIONAL SIGNAL CONTACTS (2) SUPPLIED WITH -2 AND -4 ONLY.

6 SIGNAL CONDUCTORS (2 OR 4):
18 AWG, 600V, 150°C RATED, 16/30 STRANDED,
PER UL STYLE AWM 3321.

7 LINE VOLTAGE CONDUCTORS (3):
14 AWG, 600V, 105°C RATED, COPPER 41/30 STRANDED.
PER UL STYLE AWM 1015.



8 SIGNAL CONDUCTORS (2 OR 4):
18 AWG, 600V, 105°C RATED, COPPER 16/30 STRANDED.
PER UL STYLE AWM 1015.

9 LUBRICATION: GOLD PLATED CONTACT PAD SURFACES OF SIGNAL CONTACTS ARE LUBRICATED WITH A TRANSPARENT (NON-VISIBLE) LUBRICANT TO IMPROVE DURABILITY AND PERFORMANCE. AVOID CONTACT WITH THESE SURFACES WHICH MAY RESULT IN REMOVAL OF LUBRICANT.


10 WHEN INCLUDED: SEALING GASKET (TE P/N 2213626-1)
SHIPPED IN PLACE ON ASSEMBLY AND RETAINED BY THE WIRE LEAD BUNDLE.

341.1	304.8	291.3	<div><div>7</div>AND<div>8</div></div>	Y	4 <div><div>5</div></div>	2213627-8
341.1	304.8	291.3	<div><div>7</div>AND<div>8</div></div>	Y	2	2213627-7
341.1	304.8	291.3	<div><div>3</div>AND<div>6</div></div>	Y	4 <div><div>5</div></div>	2213627-6
341.1	304.8	291.3	<div><div>3</div>AND<div>6</div></div>	Y	2	2213627-5
341.1	304.8	291.3	<div><div>7</div>AND<div>8</div></div>	N	4 <div><div>5</div></div>	2213627-4
341.1	304.8	291.3	<div><div>7</div>AND<div>8</div></div>	N	2	2213627-3
341.1	304.8	291.3	<div><div>3</div>AND<div>6</div></div>	N	4 <div><div>5</div></div>	2213627-2
341.1	304.8	291.3	<div><div>3</div>AND<div>6</div></div>	N	2	2213627-1
C	A	B	WIRE STYLE	GASKET <div><div>10</div></div>	SIGNAL CONTACTS QUANTITY	PART NO.
OVERALL LENGTH	WIRE LENGTH					


NEW PRODUCT
PRELIMINARY
IN DEVELOPMENT

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 07APR2015 CHK RAVI.S		 TE Connectivity REL IN VARY	
DIMENSIONS: mm 		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±: 1 PLC ±: 2 PLC ±: 3 PLC ±: 4 PLC ±: ANGLES ±:			
MATERIAL		FINISH		PRODUCT SPEC 108-32059	
-		-		APPLICATION SPEC 114-32148	
-		-		SIZE A2	
		Customer Drawing		CAGE CODE -	
				DRAWING NO C-2213627	
				RESTRICTED TO -	
				SCALE 1:2	
				SHEET 1 of 3	
				REV 6	

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-



TYPE	POSITION #	WIRE COLOR
POWER	1	BLACK
POWER	2	WHITE
POWER	3	RED
SIGNAL	4	VIOLET
SIGNAL	5	GRAY
SIGNAL	6	BROWN
SIGNAL	7	ORANGE

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN RAVLS 07APR2015	 TE Connectivity			
DIMENSIONS: mm		CHK C.GINGRICH 07APR2015				
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD C.GINGRICH 07APR2015	NAME ASSEMBLY ROTATING DIMMING RECEPTACLE (49.22mm),			
0 PLC ±-		PRODUCT SPEC	-			
1 PLC ±-		108-32059	SIZE A2			
2 PLC ±-		APPLICATION SPEC	CAGE CODE -			
3 PLC ±-		114-32148	DRAWING NO C-2213627			
4 PLC ±-		WEIGHT -	RESTRICTED TO -			
ANGLES ±-		Customer Drawing	SCALE 1:2			
FINISH			SHEET 2 OF 3			
-			REV 6			
-						


NEW PRODUCT
PRELIMINARY
IN DEVELOPMENT

THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION		20
© COPYRIGHT 20	BY -	ALL RIGHTS RESERVED.		

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-	SEE SHEET 1	-	-	-

IF THE LOCK RING BECOME SEPARATED FROM THE INNER HOUSING ASSEMBLY, FOLLOW THE THESE STEPS TO SNAP IT BACK INTO PLACE

TO ASSEMBLE THE LOCK RING ONTO THE INNER HOUSING, THESE STEPS MUST BE FOLLOWED.



STEP 1: ALIGN THE TE LOGO WITH ONE OF THE SCREW HOLES ON THE LOCK RING.

STEP 2: SNAP THE LOCK RING ONTO THE INNER HOUSING ASSEMBLY

STEP 3: TURN THE LOCK RING FULLY CLOCKWISE UNTIL IT STOPS (THE NORTH INDICATOR WILL BE ADJACENT TO ONE OF THE SCREW HOLES IN THE LOCK RING)

NEW PRODUCT
PRELIMINARY
IN DEVELOPMENT

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN RAVL.S 07APR2015	TE Connectivity			
DIMENSIONS: mm		CHK C.GINGRICH 07APR2015				
		APVD C.GINGRICH 07APR2015	NAME ASSEMBLY ROTATING DIMMING RECEPTACLE (49.22mm), -			
		PRODUCT SPEC 108-32059	SIZE A2			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC 114-32148	CAGE CODE -		DRAWING NO C-2213627	
MATERIAL - -		WEIGHT -	RESTRICTED TO -		SCALE 1:2	
		Customer Drawing	SHEET 3 OF 3		REV 6	