

CKF SEALED ROTARY SWITCH

GENERAL ELECTRICAL & MECHANICAL SPECIFICATION

Switch Rating:	150mA @ 250V ac/dc resistive load 1A @ 24V dc resistive load
Life:	>10,000 Cycles
Operating Temperature:	-30°C to +85 °C
Proof Voltage:	1,500Vac (Initial)
Insulation Resistance:	>999 MΩ at 500Vdc (Initial)
Contact Resistance:	<20 mΩ (initial)
Operating Torque (nominal)	Standard 10.5 ± 1 N cm Light Action 5.5 ± 0.5 N cm
End Stop Torque (nominal):	0.80 Nm
Moulding Material:	Polyamide 6.6 G.F. V0 RATED
Contact/Terminal Material:	Brass CZ108 Ag Plated


RoHS COMPLIANT



GENERAL FEATURES & OPTIONS


- Made in UK
- Cost effective single wafer switch
- Moulded 27.5mm diameter
- Standard 30° indexing
- Solder or Printed Circuit Board Terminals
- Up to 4 poles per switch
- Maximum 12 positions
- Moulded in UL94 V0 material.
- Optional reinforcement ring.
- Shorting (make before break 30° indexing only) or non shorting (break before make) contacts.
- Special options: 60° or 90° indexing, continuous rotation. Fixed stop, gold flash or gold plated contacts, and spindles with special flats.
- CKF same form, fit & function to the CK range
- Dampened indexing & reduced shaft play gives smooth feel.
- Front panel sealed to IP65

CKF ROTARY SWITCH SPECIFICATION SHEET



BASIC TYPES	SPINDLE DIAMETER	SPINDLE LENGTH FROM MOUNTING FACE	8mm LONG BUSH	SPINDLE FLAT LENGTH	ANGLE OF SPINDLE FLAT	SPINDLE FLAT THICKNESS
IMPERIAL	6.35mm	38mm	9.52 x 32TPI	30mm	90°	5.5mm
METRIC	6.00mm	50mm	M10 x 0.75	No Flat	---	---

CKF ROTARY SWITCH



IMPORTANT WAFERS FLATS & SLOTS VIEWED FROM THE FRONT OF SWITCH IN EXTREME ANTICLOCKWISE POSITION (POSITION 1)

SPINDLE FLAT ANGLE - AVAILABLE IN 15° INCREMENTS

SCREWDRIVER SLOT - AVAILABLE IN 45° INCREMENTS




ORDERING CODE FOR NON-STANDARD SWITCHES

EXISTING CK PARTS MAY BE ORDERED AS CKF TYPE BY CHANGING PART NUMBER TO START WITH CKF

C			K			F																				
												SPINDLE LENGTH FMF IN FULL MM														
Index Angles & NO. OF POLES			NO OF WAYS (POSITIONS)					MBB or BBM	Contact Type	Contact Plating		SPINDLE DIAM.	SPINDLE FLAT DEPTH	BUSH DIAM.	LENGTH OF SPINDLE FLAT				ANGLE OF FLAT (°)							
A	30°	1Pole	A	2		A	BBM	Solder	SILVER		A	6mm	Nil	M10	A	2	N	15	A	0	N	195				
B		2	B	3		B	MBB	Solder			B	6mm	5mm	M10	B	3	O	No Flat	B	15	O					
C		3	C	4		C	BBM	PCB			C	6.35mm	Nil	9.52 mm	C	4	P	16	C	30	P	210				
D		4	D	5		D	MBB	PCB			D	6.35mm	5.5mm	9.52 mm	D	5	Q	17	D	45	Q	225				
E	60°	1Pole	E	6		E	BBM	Solder	GOLD PLATE		E				E	6	R	18	E	60	R	240				
F		2	F	7		F	MBB	Solder			F				F	7	S	19	F	75	S	255				
G		3	G	8		G	BBM	PCB			G				G	8	T	20	G	90	T	270				
H		4	H	9		H	MBB	PCB			H				H	9	U	21	H	105	U	285				
I	90°	1Pole	I	10		I	BBM	Solder	GOLD FLASH		I				I	10	V	22	I	120	V	300				
J		2	J	11		J	MBB	Solder			J				J	11	W	23	J	135	W	315				
K		3	K	12		K	BBM	PCB			K				K	12	X	24	K	150	X	330				
			Z	No Stop		L	MBB	PCB			L				L	13	Y	25	L	165	Y	345				

PLEASE COMPLETE THE SPECIFICATION DRAWING IF YOUR DETAILS CANNOT BE FULLFILLED BY USING THE ORDERING CODE & CONFIRM WITH LORLIN SALES BEFORE ORDERING. TOOLING CHARGES CAN APPLY FOR SPINDLES THAT DO NOT HAVE FLATS THAT RUN THE FULL SPINDLE LENGTH




CUSTOMER TO COMPLETE OR DELETE AS REQUIRED

	A	B	C
IMPERIAL	Ø6.35		Ø9.52 x 32TPI
METRIC	Ø6.00		M10 x 0.75


	D	E	F
IMPERIAL			
METRIC			

INDEXING




1 POLE

INDEXING




2 POLE

INDEXING



3 POLE

INDEXING



4 POLE

POSITIONS					POSITIONS					POSITIONS					POSITIONS				
MBB	BBM	SOL	PCB		MBB	BBM	SOL	PCB		MBB	BBM	SOL	PCB		MBB	BBM	SOL	PCB	

IMPORTANT! WAFERS FLATS & SLOTS VIEWED FROM THE FRONT OF SWITCH IN EXTREME ANTICLOCKWISE POSITION (POSITION 1)

SPECIAL REQUIREMENTS

OPTIONS Stops are adjustable 2-12 positions. Continuous rotation (No Stops) available. Make before break (MBB) or Break before Make (BBM) rotors available. Solder Tag (SOL) or PCB pin (PCB) – indicate on wafer.

CUSTOMER:

DATE:

CUSTOMER REFERENCE NUMBER: