




LOC	DIST	REVISIONS				
AF	50	P	LTR	DESCRIPTION	DATE	APVD
			A2	REVISED PER ECR-11-006644	05APR11	HMR GJ

- 1
- CONTINUOUS STRIP ON REELS
- 2
- WIRE RANGE FOR NEW APPLICATIONS: 3.75–5.07mm²[7400–10,000CMA]
(WIRE RANGE APPROVED FOR APPLICATIONS IMPLEMENTED
PRIOR TO 2005: 4000–10,000 CMA).
- 3
- CRIMP WIDTH: 4.57[.180]F TYPE. CRIMP HEIGHT IN INCHES
(+/- .002)=(TOTAL CMA OF WIRES + 20044)/288890.



62357-1

PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN jr ruth	24NOV04	 TE Connectivity			
DIMENSIONS: mm [INCHES]		CHK G PORTA	24NOV04	NAME SPLICE			
	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD G PORTA	24NOV04				
		PRODUCT SPEC —					
		APPLICATION SPEC 114-2088					
		WEIGHT —					
MATERIAL TEMP 1 BTRASS		FINISH —		SIZE A3	CAGE CODE 00779	DRAWING NO C-62357	RESTRICTED TO —
CUSTOMER DRAWING				SCALE 1:1	SHEET 1 OF 1	REV A2	