

A. System Overview

UL® cUL® Sta-Strap® Clamp Ties

- Natural nylon material for indoor use
- Weather resistant material has greater resistance to damage caused by ultraviolet light – indoor or outdoor use
- Heat stabilized material for high temperature applications up to 239°F (115°C) – indoor use
- Design allows for bundling before or after screwing clamp in place


- Exclusive two-piece design offers the lowest threading force in the industry
- Used to secure a cable bundle to another surface such as a control panel, communication rack, wall or ceiling
- Only clamp tie that is releasable prior to final tensioning



SSC2S-S10-C



SSC2S-S10-M0



B1. Cable Ties

B2. Cable Accessories

B3. Stainless Steel Ties

C1. Wiring Duct

C2. Surface Raceway

C3. Abrasion Protection

C4. Cable Management

D1. Terminals

D2. Power Connectors

D3. Grounding Connectors

E1. Labeling Systems

E2. Labels

E3. Pre-Printed & Write-On Markers

E4. Permanent Identification

E5. Lockout/Tagout & Safety Solutions

F. Index

| Part Number | Length | | Width | | Thickness | | Nominal Hole Dia. | | Screw Size | Metric Screw Size | Max. Bundle Dia. | | Min. Loop Tensile Str. | | Recommended Installation Tool | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-------------|--------|----|-------|----|-----------|----|-------------------|----|------------|-------------------|------------------|----|------------------------|---|-------------------------------|----------------|----------------|
| | In. | mm | In. | mm | In. | mm | In. | mm | | | In. | mm | Lbs. | N | | | |

Nylon 6.6

Standard Cross Section

| | | | | | | | | | | | | | | | | | |
|--------------------|------|-----|------|-----|------|-----|------|-----|-----|----|------|-----|----|-----|--|-----|------|
| SSC2S-S6-C | 7.4 | 187 | .180 | 4.6 | .045 | 1.1 | .148 | 3.8 | #6 | M3 | 1.75 | 45 | 50 | 222 | GTS, GTSL, GS2B, GTH, GS4H, PTS, PTH, PPTS, STS2, STH2 | 100 | 1000 |
| SSC2S-S10-C | 7.4 | 187 | .180 | 4.6 | .045 | 1.1 | .200 | 5.1 | #10 | M5 | 1.75 | 45 | 50 | 222 | | 100 | 1000 |
| SSC4S-S10-C | 15.7 | 398 | .180 | 4.6 | .045 | 1.1 | .200 | 5.1 | #10 | M5 | 4.00 | 102 | 50 | 222 | | 100 | 500 |

Light-Heavy Cross Section

| | | | | | | | | | | | | | | | | | |
|-------------|------|-----|------|-----|------|-----|------|-----|-----|----|------|-----|-----|-----|------------------------------------|----|-----|
| SSC4H-S25-L | 15.6 | 395 | .300 | 7.6 | .065 | 1.7 | .260 | 6.6 | 1/4 | M6 | 4.00 | 102 | 120 | 534 | GTH, GS4H, GS4EH, PTH, STH2, ST3EH | 50 | 500 |
|-------------|------|-----|------|-----|------|-----|------|-----|-----|----|------|-----|-----|-----|------------------------------------|----|-----|

Weather Resistant Nylon 6.6

Standard Cross Section

| | | | | | | | | | | | | | | | | | |
|---------------------|------|-----|------|-----|------|-----|------|-----|-----|----|------|-----|----|-----|--|------|-------|
| SSC2S-S6-M0 | 7.4 | 187 | .180 | 4.6 | .045 | 1.1 | .148 | 3.8 | #6 | M3 | 1.75 | 45 | 50 | 222 | GTS, GTSL, GS2B, GTH, GS4H, PTS, PTH, PPTS, STS2, STH2 | 1000 | 10000 |
| SSC2S-S10-M0 | 7.4 | 187 | .180 | 4.6 | .045 | 1.1 | .200 | 5.1 | #10 | M5 | 1.75 | 45 | 50 | 222 | | 1000 | 10000 |
| SSC4S-S10-M0 | 15.7 | 398 | .180 | 4.6 | .045 | 1.1 | .200 | 5.1 | #10 | M5 | 4.00 | 102 | 50 | 222 | | 1000 | 5000 |

Light-Heavy Cross Section

| | | | | | | | | | | | | | | | | | |
|--------------|------|-----|------|-----|------|-----|------|-----|-----|----|------|-----|-----|-----|------------------------------------|-----|------|
| SSC4H-S25-D0 | 15.6 | 395 | .300 | 7.6 | .065 | 1.7 | .260 | 6.6 | 1/4 | M6 | 4.00 | 102 | 120 | 534 | GTH, GS4H, GS4EH, PTH, STH2, ST3EH | 500 | 2500 |
|--------------|------|-----|------|-----|------|-----|------|-----|-----|----|------|-----|-----|-----|------------------------------------|-----|------|

Heat Stabilized Nylon 6.6

Standard Cross Section

| | | | | | | | | | | | | | | | | | |
|----------------------|-----|-----|------|-----|------|-----|------|-----|-----|----|------|----|----|-----|--|------|-------|
| SSC2S-S10-M30 | 7.4 | 187 | .180 | 4.6 | .045 | 1.2 | .200 | 5.1 | #10 | M5 | 1.75 | 45 | 50 | 222 | GTS, GTSL, GS2B, GTH, GS4H, PTS, PTH, PPTS, STS2, STH2 | 1000 | 10000 |
|----------------------|-----|-----|------|-----|------|-----|------|-----|-----|----|------|----|----|-----|--|------|-------|

Light-Heavy Cross Section

| | | | | | | | | | | | | | | | | | |
|---------------|------|-----|------|-----|------|-----|------|-----|-----|----|------|-----|-----|-----|------------------------------------|-----|------|
| SSC4H-S25-D30 | 15.6 | 395 | .300 | 7.6 | .065 | 1.7 | .260 | 6.6 | 1/4 | M6 | 4.00 | 102 | 120 | 534 | GTH, GS4H, GS4EH, PTH, STH2, ST3EH | 500 | 2500 |
|---------------|------|-----|------|-----|------|-----|------|-----|-----|----|------|-----|-----|-----|------------------------------------|-----|------|