

1		2		3		4	
NOTES 1. The recommended clamp torque to receptacle: 1.2N · m 2. In order to prevent screw loosening after assembly to the receptacle, wrap self-fusing tape around this component and the receptacle for stabilization. ⚠ 3. This product is a cap for JR※25WR※-※(※). It is applicable regardless of given alphabets and/or numbers shown at ※.							
1 Polyamide		(BLACK) UL94V-0		2 Silicone Rubber		(Red brown)	
NO. MATERIAL		FINISH . REMARKS		NO. MATERIAL		FINISH . REMARKS	
UNITS mm		SCALE 2 : 1	COUNT ⚠ 1	DESCRIPTION OF REVISIONS DIS-C-002972		DESIGNED WR. AJIRO	CHECKED TP. KOMATSU
DATE 13. 03. 25		APPROVED : SU. OBARA 10. 11. 04		DRAWING NO. EDC4-116400-00			
CHECKED : HY. KOBAYASHI 10. 11. 04		DESIGNED : HS. NAGANO 10. 11. 02		PART NO. JR25WRC5			
DRAWN : HS. NAGANO 10. 11. 02				CODE NO. CL114-2175-6-00			
HRS HIROSE ELECTRIC CO., LTD.				⚠ 1/1			