





0955 429 3821 741	1	M3	Black insulator	Reel Packaging: 140 connectors (See details on page2/2)			
0955 429 3822 741	1	4-40 UNC					
0955 429 6821 741	2	M3					
0955 429 6822 741	2	4-40 UNC					
0955 429 7821 741	3	M3					
0955 429 7822 741	3	4-40 UNC					
Part number	PL	Screw lock	Index designation				
	All Dimensions in mm Original Size DIN A 3		Techn. Character.		Free size tolerances		
				Det.	Name	Scale 1.5:1	D-Sub SMT, 37 poles Male, Straight with screw locks and ground pads
			Detail.	25-Oct-11	Johnson.S		
			Insp.	17-Nov-11	Steven.W		
			Stand.	17-Nov-11	Steven.W		
EC04070	17-Nov-11	Johnson.S	Zhuhai HARTING Limited			TB 09 55 429 x82x	Page 1/2
Mod.	Det.	Name				Sub.	



Detail A



See TB 09 55 429 x82x folio 1/2
for connector dimensions
and PCB layout

Packaging in accordance with
EIA 481-2.

0955 429 3821 741	1	M3	Black insulator	Reel Packaging: 140 connectors
0955 429 3822 741	1	4-40 UNC		
0955 429 6821 741	2	M3		
0955 429 6822 741	2	4-40 UNC		
0955 429 7821 741	3	M3		
0955 429 7822 741	3	4-40 UNC	Index designation	
Part number	PL	Screw lock		

			All Dimensions in mm Original Size DIN A 3			Techn. Character.			Free size tolerances		
				Dat.	Name	Scale	D-Sub SMT, 37 poles Male, Straight with screw locks and ground pads				
			Detail.	25-Oct-11	Johnson.S						
			Insp.	17-Nov-11	Steven.W						
			Stand.	17-Nov-11	Steven.W						
			Zhuhai HARTING Limited				TB 09 55 429 x82x			Page 2 / 2	
EC04070	17-Nov-11	Johnson.S					Sub.				
Mod.	Dat.	Name									