






Jul.1.2019 Copyright 2019 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.




B-B



A-A



- NOTES
- 1 THIS PRODUCT IS APPLY TO THE WIRE #20 TO #25(WIRE JACKET DIAMETER $\phi 1.7$ MAX.)
 - 2 PER PACK:100 CONTACTS.
 - 3 CONTACT AREA : GOLD PLATING $0.2\mu\text{m}$ min.
TERMINAL AREA : NICKEL PLATING $2\mu\text{m}$ min.
UNDER PLATING : NICKEL $2\mu\text{m}$ min.

1	PHOSPHOR BRONZE	3						
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS		
UNITS mm		SCALE 10 : 1	COUNT  5	DESCRIPTION OF REVISIONS DIS-C-001336		DESIGNED DS. MATSUNE	CHECKED SU. OBARA	DATE 09. 06. 17
 HIROSE ELECTRIC CO., LTD.			APPROVED : MO. SATOH	08. 11. 12	DRAWING NO. EDC3-116078-00			
			CHECED : TH. KAMEYA	08. 11. 11	PART NO. HR34B-SC1-111			
			DESIGNED : DS. MATSUNE	08. 11. 11	CODE NO. CL134-0051-7-00			
			DRAWN : DS. MATSUNE	08. 11. 11	 1/1			