








PRODUCT NUMBER	PLATING PERFORMANCE LEVEL	APPLICATION
10064100-502ZZZ	TELCORDIA UE	STANDARD
10064100-502ZZZLF		LEAD FREE
10064100-902ZZZ	TELCORDIA CO	STANDARD
10064100-902ZZZLF		LEAD FREE




mat'l code				tolerances unless otherwise specified				CUSTOMER			
ltr	ecn no.	dr	date	linear	.XX ±.01				COPY		
A	V05-1105	LP	12/8/05		.XXX ±.005				projection		
B	V06-0492	DCH	2006-05-23		.XXX ±.0020				title		
C	V07-0185	DCH	2007-4-23	angles	0° ±2°				product family		
				dr	L. POTTEIGER	12/8/05			METRAL 1000		
				enrg	J. VOLSTORF	12/8/05			code		
				chr	J. VOLSTORF	12/8/05			213		
				appd	J. VOLSTORF	12/8/05			sheet		
sheet index				revision	C	C	C	C	1 of 4		
				sheet	1	2	3	4			



PRODUCT NUMBER
SEE SHEET 1

PRESS-FIT HOLES	OPTION 1	OPTION 2
HOLE DIAMETER AFTER PLATING	0.45-0.55	0.48-0.57
DRILLED HOLE	0.60±0.02	0.60±0.02
COPPER PLATING	0.025 MIN-0.050 MAX.	0.025 MIN-0.050 MAX.
SnPb PLATING	0.005-0.015	---



RECOMMENDED PCB HOLE PATTERN
(COMPONENT SIDE)
SEE NOTE 10 & 14

mat'l code				--		tolerances unless otherwise specified		CUSTOMER		 www.fciconnect.com	
ltr	ecn no.	dr	date	linear	.XX ±.01		COPY			title SIGNAL HEADER 2 MOD, 8 ROW MINI PRESS-FIT, STD	
C	-	-	-		.XXX ±.005		projection				
					.XXXX ±.0020						
				angles	0° ±2°				product family METRAL 1000		code
					dr	L.POTTEIGER	12/8/05	scale		size	dwg no
				enrg	J. VOLSTORF	12/8/05	2:1		A	10064100	sheet
				chr	J. VOLSTORF	12/8/05					2
				appd	J. VOLSTORF	12/8/05					
sheet index	revision sheet										



DIM A	PIN CODES
5.00	1
5.75	2
6.50	3
7.25	4
8.00	*19

* CURRENTLY NOT AVAILABLE


SPECIAL LOAD PRODUCT #	ROW	PIN CODES
10064100-X02001 SEE NOTE 18 LEAD FREE OPTION	H	1
	G	
	F	
	E	
	D	
	C	
	B	
	A	
	GND	1

NOTES:

- SEE APPLICATION SPECIFICATION GS-20-014 FOR INFORMATION ON AVAILABLE TOOLING, CIRCUIT BOARD DESIGN CONSIDERATIONS, REPAIR PROCEDURES AND PRODUCT OFFERINGS. SEE PRODUCT SPECIFICATION GS-12-185.
- UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS AND TOLERANCES ARE IN ACCORDANCE WITH ASME Y14.5, 1994
- HOUSING MATERIAL: LIQUID CRYSTAL POLYMER, 30% GLASS FILLED, FLAME RETARDANT PER UL 94-V0.
- PIN MATERIAL: PHOSPHOR BRONZE
- GROUND SPRING MATERIAL: PHOSPHOR BRONZE
- STRIPLINE SHIELD MATERIAL: PHOSPHOR BRONZE
- PLATING INFORMATION: PLATING IN CONTACT AREA MEETS PERFORMANCE LEVEL SHOWN IN TABLE ON SHEET 1. PLATING ON "LF" TAILS IS Sn ONLY; OTHERS ARE SnPb.
- DIMENSIONAL RESTRICTIONS OF PINS IN HEADERS.
 - FOR USE WITH METRAL 4000 RECEPTACLES.
DIM A : 5.00mm MIN, 6.50mm MAX FOR ROWS A,B,D,E,G,H
DIM A : 5.00mm MIN, 8.00mm MAX FOR ROWS C-F
DIM A : 5.00mm MIN, 5.75mm MAX FOR ROWS GND
 - FOR USE WITH METRAL 1000 RECEPTACLES/
DIM A : 5.00mm MIN, 8.00mm MAX FOR ROWS A,B,C,D,E,F,G,H
DIM A : 5.00mm MIN, 5.75mm MAX FOR ROW GND
- THE MIN PCB THICKNESS FOR FRONT PLUG-UP APPLICATIONS IS 1.6mm.
- THE "CONNECTOR OUTLINE" IS THE MIN OUTLINE REQUIRED. TO DETERMINE THE OUTLINE NECESSARY TO PERMIT THE VARIOUS TYPES OF REPAIR OPERATIONS, SEE APPLICATION SPECIFICATION GS-20-010.
- CURRENT RATING : 1 AMP PER PIN
- TEMPERATURE RANGE : -55°C TO +105°C
- P/N 10064100-X 02 ZZZ



- AVOID TRACES ON TOP OF BOARD DUE TO EXPOSED GROUND SHIELDS.
- FOR FRONT PLUG-UP APPLICATIONS, IF THE SURROUNDING PINS ARE NOT USED FOR POWER, THEN EACH PIN CAN CARRY 3 AMPS. IF THE SURROUNDING PINS ARE USED FOR POWER, THEN EACH PIN CAN CARRY 1 AMP.
- AFTER INSERTION INTO, CIRCUIT BOARD WITH QUALIFIED TOOL.
- THE PRODUCTS WHERE THE PART NUMBER ENDS IN 'LF' MEET THE EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008. ALL PRODUCTS WILL WITHSTAND EXPOSURE TO 260°C FOR 60 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.
- FOR LEAD FREE PART NUMBERS, ADD AN 'LF' SUFFIX. EXAMPLE: 10064100-X02001LF.


mat'l code				tolerances unless otherwise specified		CUSTOMER		www.fciconnect.com				
ltr	ecr no.	dr	date	linear	.XX ±.01	projection		titleSIGNAL HEADER 2 MOD, 8 ROW MINI PRESS-FIT, STD				
C	-	-	-		.XXX ±.005							
				.XXXX ±.0020								
				angles	0° ±2°							
				dr	L.POTTEIGER	12/8/05		product family		METRAL 1000		code
				enrg	J. VOLSTORF	12/8/05		size		dwg no		213
				chr	J. VOLSTORF	12/8/05	scale		A		10064100	sheet
				appd	J. VOLSTORF	12/8/05	2:1					3
sheet index		revision sheet										

This document is the property of and embodies
CONFIDENTIAL and PROPRIETARY information of FCI.
No part of the information shown on this
document may be used in any way or disclosed
to others without the written consent of FCI.
Copyright FCI.




PRODUCT NUMBER

SEE SHEET 1



RECOMMENDED TRACK AND ANTIPAD DIMENSIONS
SCALE 4:1

mat'l code				tolerances unless otherwise specified		CUSTOMER		 www.fciconnect.com	
ltr	ecn no.	dr	date	linear	.XX ±.01	COPY		title SIGNAL HEADER 2 MOD, 8 ROW MINI PRESS-FIT, STD	
C	-	-	-		.XXX ±.005	projection			
					.XXXX ±.0020				
				angles	0° ±2°			product family METRAL 1000	
		dr		J. POTTEIGER	12/8/05	scale 2:1		size	code
		enrg		J. VOLSTORF	12/8/05			dwg no	213
		chr		J. VOLSTORF	12/8/05			A 10064100	
		appd		J. VOLSTORF	12/8/05				
sheet index	revision sheet								

cage code 22526

Pro/E

PDM: Rev:C

STATUS: Released

Printed: Nov 16, 2011