

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Fuse plug, Nominal current: 6.3 A, Length: 33.1 mm, Width: 6.1 mm, Height: 45.7 mm, Color: black

The illustration shows the version without LED/light indicator



### **Key Commercial Data**

Packing unit	1 pc
GTIN	4 017918 010300
Weight per Piece (excluding packing)	5.8 g
Custom tariff number	85363010
Country of origin	Poland

#### Technical data

#### General

Note	If the fuse is defective, the downstream circuit is not off load
Color	black
Insulating material	PA
Flammability rating according to UL 94	V2

#### **Dimensions**

Width	6.1 mm
Length	33.1 mm

#### General

Fuse	G / 5 x 20
Insulating material group	CTI 600
Nominal current I <sub>N</sub>	6.3 A



#### Technical data

#### General

Nominal voltage U <sub>N</sub>	250 V
--------------------------------	-------

#### Connection data

Connection	on method	Plug connection
Cominocus	in metricu	1 lag comicodon

#### Standards and Regulations

Connection in acc. with standard	CUL
Flammability rating according to UL 94	V2

#### Classifications

#### eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141149
eCl@ss 7.0	27141149
eCl@ss 8.0	27142001

#### **ETIM**

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002018
ETIM 5.0	EC000036

#### **UNSPSC**

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

## Approvals

#### Approvals

Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized



Approvals		
Ex Approvals		
Approvals submitted		
Approval details		
UL Recognized <b>5</b>		
Nominal current IN	0.2.4	
Nominal voltage UN	6.3 A 300 V	
Nonmal voltage on		
cUL Recognized		
Nominal current IN	6.3 A	
Nominal voltage UN	300 V	
	<u> </u>	
EAC		
cULus Recognized CALUS		

#### Accessories

Accessories

Documentation

Mounting material - ST-IL - 3039900

Operating decal for the ST terminal block





## Accessories

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com