



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Interface**

According to IEC 60169-10, CECC 22130, US MIL-C-39012

**Documents**

PCB layout B 30

**Material and plating**

**Connector parts**

Center contact  
Outer contact  
Dielectric

**Material**

Brass  
Brass  
PTFE

**Plating**

AuroDur®, gold plated  
AuroDur®, gold plated

**Electrical data**

|                           |   |
|---------------------------|---|
| Impedance                 | 50 Ω  |
| Frequency                 | DC to 4 GHz                                 |
| Return loss               | ≥ 25 dB, DC to 1 GHz<br>≥ 18 dB, 1 to 4 GHz |
| Insertion loss            | ≤ 0.1 x √f(GHz) dB                          |
| Insulation resistance     | ≥ 1x10 <sup>3</sup> MΩ                      |
| Center contact resistance | ≤ 5 mΩ                                      |
| Outer contact resistance  | ≤ 2.5 mΩ                                    |
| Test voltage              | 750 V rms, 50 Hz, at sea level              |
| Working voltage           | ≤ 250 V rms, 50 Hz, at sea level            |
| Contact current           | 1.5 A DC typ.                               |
| RF-leakage                | ≥ 55 dB up to 1 GHz                         |

- Connector only, VSWR in application depends decisive on PCB layout -

**Mechanical data**

|                                   |                       |
|-----------------------------------|-----------------------|
| Mating cycles                     | ≥ 500                 |
| Center contact captivation: axial | ≥ 10 N                |
| Engagement force                  | ≤ 63 N                |
| Disengagement force               | 8 N min. to 63 N max. |

**Environmental data**

|                            |                                 |
|----------------------------|---------------------------------|
| Temperature range          | -55°C to +155°C                 |
| Thermal shock              | MIL-STD-202, Meth. 107, Cond. B |
| Vibration                  | MIL-STD-202, Meth. 204, Cond. B |
| Corrosion                  | MIL-STD-202, Meth. 101, Cond. B |
| Moisture resistance        | MIL-STD-202, Meth. 106          |
| Max. soldering temperature | IEC 61760-1, +260°C for 10 sec. |
| RoHS                       | compliant                       |

**Tooling**

N/A

**Suitable cables**

N/A

**Weight**

|        |           |
|--------|-----------|
| Weight | 0.7 g/pce |
|--------|-----------|

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

| Draft  | Date     | Approved          | Date     | Rev. | Engineering change number  | Name      | Date          |
|--|----------|-------------------|----------|------|--|-----------|---------------|
| A. König   | 25/10/06 | Sa. Krautenbacher | 20.03.14 | d00  | 14-0352  | T. Krojer | 20.03.14      |
| Rosenberger Hochfrequenztechnik GmbH & Co. KG<br>P.O.Box 1260 D-84526 Tittmoning Germany<br><a href="http://www.rosenberger.de">www.rosenberger.de</a> |          |                   |          |      | Tel.: +49 8684 18-0<br>Fax: +49 8684 18-499<br>email: <a href="mailto:info@rosenberger.de">info@rosenberger.de</a> |           | Page<br>2 / 2 |