CAD GENERATED DRAWING - NO PENCIL CHANGES ALLOWED

SECTION A-A

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

DENOTES CRITICAL CHARACTERISTICS.

DENOTES CPK DIMENSIONS.-MINIMUM CPK VALUE

DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.

DENOTES CP DIMENSIONS.-MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ACCOUNT FOR MAXIMUM TOOL LIFE.

NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M
2	-904-126	BRASS ALLOY 270	1000	EA
1	SEE CHART	TIN PLATING	.018200	LB

BILL OF MATERIAL

LTR	REVISION	CHK	APD
M	39010C- REVISED & REDRAWN ON NEW FORMAT 3/3/98 JMB		

COPIES TO: 1 9 18 / 2 10 19 / 3 12 20 / 4 13 21 / 5 14 23 / 6 15 33 / 7 16 43 / 8 17 53

MATL SPEC: BRASS, CDA 260 OR CDA 270 BRASS WIRE

FINISH: .0003/.0006 TIN PLATE PER ES-001002B

DRW: JMB DATE 1/23/98

CHK: DATE

APPD: DATE

SCALE 4=1

SUPER DRW

RAW STK WT LBS/M

TOLERANCE UNLESS OTHERWISE SPECIFIED
TWO PLACE DEC ±.01 FRACTION ±
THREE PLACE DEC ±.005 ANGULAR ±1°

TITLE: CONTACT RIVET

Littelfuse®
DES PLAINES, ILLINOIS 60016

REVISION: M

DRWG. NO. -904-126

UNCONTROLLED DOCUMENT