# **ALUMINUM ELECTROLYTIC CAPACITORS**




Wide Temperature Range, Miniature Type Permissible Abnormal Voltage



- Improved safety feature for abnormally excessive voltage.
- High ripple current product.
- Compliant to the RoHS directive (2011/65/EU).






### ■ Specifications

Item	Performance Characteristics									
Category Temperature Range	-40 to +105°C									
Rated Voltage Range	200V, 400V									
Rated Capacitance Range	4.7 to 330µF									
Capacitance Tolerance	±20% at 120Hz, 20°C									
Leakage Current	After 1 minute's application of rated voltage at 20°C, leakage current is 0.04CV+100 (μA) or less.									
Tangent of loss angle (tan δ)	Rated voltage (V) 200 400 Measurement frequency:120Hz at 20°C tan δ (MAX.) 0.15 0.15									
	Rated voltage (V)		200		400 N		asurement frequency : 120Hz			
Stability at Low Temperature	7-2	5°C / Z+20°C	3		8					
	Impedance ratio ZT / Z20 (MAX.) Z-4	0°C / Z+20°C	6		10					
Endurance	The specifications listed at right shall be capacitors are restored to 20°C after D.C ripple current is applied for 2000 hours a voltage shall not exceed the rated voltage	apacitance chan n δ eakage current	ge	Within ±20% of the initial capacitance value 200% or less than the initial specified value Less than or equal to the initial specified value						
Shelf Life	After leaving capacitors under no load at 105°C for 1000 hours they shall meet the specified values for the endurance characteristics listed above.									
	The pressure relief vent will operate in normal conditi	ons, with no danger	rous conditor	ns su	ch as flames, ignitio	ns or o	dispersion of pieces of the capacitor and / or case.			
0 ( ) 0 (	voltage (V)	Test co				nditions				
Safety Performance	voltage (v)		Limited DO	C cu	rrent		Test Voltage			
	200	4A (5A : 330μF)					300VDC and 375VDC			
	400	2A (4A : 100μF or more) 500VDC					500VDC and 600VDC			
Marking	Printed with white color letter on dark bro	wn sleeve.								

### ■ Radial Lead Type






				(mm)
φD	10	12.5	16	18
Р	5.0	5.0	5.0	5.0
φd	0.6	0.6	0.8	0.8

※ In case L>25 for φ12.5 (D) case sizes, lead diameter φ0.8 (d) will be applied.

• Please refer to page 20 about the end seal configuration.

# Type numbering system (Example : 200V 220 $\mu\textrm{F})$



Configuration									
φD	Pb-free leadwire Pb-free PET sleeve								
10	PD								
12.5 to 18	HD								

#### ■ Dimensions

	V	200 (2D)						400 (2G)									
Cap.(µF)	ode <sup>\$\phi D\$</sup>	φ10	)	ф12.	5	φ16		φ18		φ10	)	ф12.	5	φ16		φ18	}
4.7	4R7		l I		l		l			10 × 9	60		l I				
22	220				l						l	12.5 × 20	165				
27	270				l I						i i	12.5 × 25	200				
33	330	10 × 20	160								1			16 × 20	225		
39	390				l I		l I				1			16 × 25	255	▲18 × 20	255
47	470	10 × 25	195	▲12.5 × 20	195						1		1	16 × 25	290	▲18 × 20	280
56	560		I I	12.5 × 20	210		 				] 		l I	16 × 31.5	340	▲18 × 25	320
68	680		l	12.5 × 25	320		! !				1		l I	16 × 35.5	385	▲18 × 25	360
82	820			12.5 × 25	360		l I				1		1	16 × 40	435	▲18 × 31.5	430
100	101		I I	12.5 × 31.5	430	▲16×20	430				 		1			18 × 35.5	490
120	121		l I		l I		! !	!			1					18 × 40	¦ 540
150	151		İ		i i	16 × 25	460	▲18×20	460		1		i				Ī
180	181		i		i I	16 × 31.5	600	▲18×25	600		i		i				Î
220	221		İ		i i		i i	18 × 31.5	710		1		İ				Î
270	271		İ		i i		i i	18 × 35.5	890		i		i			Case size	Rated
330	331		i		i			18 × 40			i		i			Case size \$\phi D \times L (mm)	ripple

## • Frequency coefficient of rated ripple current

Frequency	50, 60Hz	120Hz	300Hz	1kHz	10kHz or more
Coefficient	0.80	1.00	1.25	1.40	1.60

Rated ripple current (mArms) at 105°C 120Hz

▲: In case of low profile type, ⑤ will be put at 12th digit of type numbering system. Please refer to page 20, 21, 22 about the formed or taped product spec. Please refer to page 4 for the minimum order quantity.

CAT.8100D