




2.40	2.60 2.20	1.55	1.96 1.57	1.30 - 1.60	22-24 AWG	ON REEL	6	1-2106123-6
2.40	2.60 2.20	1.55	1.96 1.57	1.30 - 1.60	22-24 AWG	ON REEL	4	1-2106123-3
2.40	2.60 2.20	1.55	1.96 1.57	1.30 - 1.60	22-24 AWG	LOOSE PIECE	2 3	1-2106123-2
2.40	2.60 2.20	1.55	1.96 1.57	1.30 - 1.60	22-24 AWG	ON REEL	2 3	1-2106123-1
3.01	2.80 2.40	2.05	2.32 1.92	1.70 - 2.10	18-20 AWG	ON REEL	4	2106123-3
3.01	2.80 2.40	2.05	2.32 1.92	1.70 - 2.10	18-20 AWG	LOOSE PIECE	2 3	2106123-2
3.01	2.80 2.40	2.05	2.32 1.92	1.70 - 2.10	18-20 AWG	ON REEL	2 3	2106123-1
DIM D	DIM C	DIM B	DIM A	INSULATION DIA	WIRE RANGE	REMARKS	FINISH	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.				DWN R. BROWN 04MAR2009	TE Connectivity			
				CHK A. BUCHER 04MAR2009				
DIMENSIONS: mm				APVD -	NAME			
				PRODUCT SPEC 108-2391	CONTACT, RECEPTACLE, CRIMP SNAP-IN SLIM SEAL SSL			
				APPLICATION SPEC 114-13261				
MATERIAL 1 -				WEIGHT -	SIZE A2	CAGE CODE 00779	DRAWING NO C-2106123	RESTRICTED TO -
SEE TABLE				CUSTOMER DRAWING	SCALE 10:1	SHEET 1	OF 1	REV A3