

Fuseholder Open Design, Holder for OMF 63, OMF 125 and OMT 125, SMD



125 VAC · 5 A (UL/CSA)

**Description**

- Suitable for SMD fuse-links OMF 63/OMF 125/OMT 125

Standards

- UL 512 and CSA C22.2 no. 39

Approvals

- UL File Number: E39328
 - CSA File Number: 38456

References

Packaging Details



Fuseholder to [Dummy_OMF125](#); [OMF 125](#); [OMF 63](#); [OMT 125](#); [OSU 125](#)**Weblinks**

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [Approvals](#), [CE declaration of conformity](#), [RoHS](#), [CHINA-RoHS](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [Detailed request for product](#)

Technical Data

Fuse-Link	OMx 63/125 Fuse
Mounting	PCB
Terminal	Solder SMT
Rated Voltage	125VAC
Rated Current	5A (UL/CSA)
Degree of Protection	IP 00
Admissible Ambient Air Temp.	-40°C to 85°C
Climatic Category	40/085/21 acc. to IEC 60068-1
Material: Socket	Thermoplastic, Beige, UL 94V-0
Material: Terminals	Tin-Plated Copper Alloy
Unit Weight (Socket/Cap)	3.9 g
Storage Conditions	0°C to 60°C, max. 70% r.h.
Product Marking	Approvals

Soldering Methods	Reflow
Solderability	245°C / 3 sec acc. to IEC 60068-2-20, Test Td
Resistance to Soldering Heat	260°C / 10 sec acc. to IEC 60068-2-20, Test Td
Dielectric Strength	> 3kV (50Hz; 1 min)
Impulse Withstand Voltage	> 4kV between L-N
Insulation Resistance	> 10MΩ between L-N (500VDC; 1 min)
Overvoltage Category	I - III acc. to IEC 60664-1
Pollution Degree	1 - 3 acc. to IEC 60664-1

Dimensions


Soldering pads

Variants

Holder	Order Number
•	0031.7701.xx

Packaging Unit

- .xx = .11 Plastic Bag (100 pcs.)
 - .xx = .22 Blister Tape 33 cm Reel (750 pcs.)
 - .xx = .23 Blister Tape 33 cm Reel (1500 pcs.)
-