



1471-9 (3/13)

	2		REVI	1 ISIONS		
g leads		P LTR -	DESC SEE SHEET 1	RIPTION	DATE DWN APVD	>
g leads FF)			Model	POS.I	POS.2	
			N o . PB7	ON ON	MOM(OFF)	
			CONNECTED TERMINALS	CLOSE	OPEN	
			SCHEMATIC			
			S <u>W </u>	TCH FUN	<u>CTION</u>	
_						
Ą						
7.30 [.287]						
4						
I						
. 90 ^{+0.05} -0.03 508 ^{+.002}]						
				2 TERMIN	AL 2 BLACK	
3.60+0.00				1 TERMIN NO. DESCRIF	AL 1 BLACK	
535 ⁺ .000]	Снк	<u>AVI.S</u> K 22FE ALEXANDER SHA	ARAF I		E Connectivity	
	mm[INCHES]	ALEXANDER SHA	B2018 ARPE SWITCH, FLYING	PUSHBUTTON, LEADS WITH HE	HIGH CAP NO LED EAT SHRINK, ON-(OFF)	,
	APP APP ANGLES ±5°	PLICATION SPEC - IGHT _	SIZE CAGE CODE	C = 2329359	/ UN - (UFF) RESTRICTED T	
	CU:	STOMER DRAWIN		SCALE 3:2	SHEET 2 OF 3 REV 1	

Г	THIS DRAWING IS UNPUBLISHED	<u> </u>			L					
╞	(C) COPYRIGHT.copyright_dBYe - ALL RIGHTS RESERVED.							REVISIONS	DATE DWN APV	<u> </u>
							P LTR		DATE DWN APV	
							- SEE SHEE			_
										D
										C
										C
										В
					Н	IGH, SHINY BLUE	N / A	PB7B2HS7M1CAL00Y500	1-2329359-0	\dashv
						GH, SHINY GREEN	N / A	PB7B2HS6M1CAL00Y500	2329359-9	
			ON-(OFF) MOMENTARY			GH, SHINY YELLOW	N / A	PB7B2HS5M1CAL00Y500	2329359-8	\neg
						IGH, SHINY RED	N / A	PB7B2HS3M1CAL00Y500	2329359-7	
					ΗΙ	GH, SHINY BLACK	N / A	PB7B2HS2M1CAL00Y500	2329359-6	
		SINGLE POLE -		- FLYING LEADS WITH HEAT SHRINK		IGH, SHINY BLUE	N / A	PB6B2HS7M1CAL00Y500	2329359-5	
						GH, SHINY GREEN	N / A	PB6B2HS6M1CAL00Y500	2329359-4	
			OFF-(ON) MOMENTARY			GH, SHINY YELLOW	N / A	PB6B2HS5M1CAL00Y500	2329359-3	
						IGH, SHINY RED	N / A	PB6B2HS3M1CAL00Y500	2329359-2	
						GH, SHINY BLACK	N / A	PB6B2HS2M1CAL00Y500	2329359-1	
		POLE	THROW	TERMINAL TYPE		AP TYPE & COLOR	LED COLOR TE	DESCRIPTIVE PART NUMBE	RIPART NUMBER	_
				THIS [DRAWING IS A (CONTROLLED DOCUMENT.	L.S 2255B2010	TE TE	onnectivity	
					DIMENSIONS:	TOLERANCES UNLESS	(ANDER SHARPE			A
					[INCHES]	OTHERWISE SPECIFIED:	(ANDER SHARPE	SWITCH, PUSHBUTTON, HI	GH CAP NO LED	,
					<u> </u>	O PLC ±- PRODUC1 1 PLC ±0.4[.016] - 2 PLC ±0.25[.010] - 3 PLC ±- APPLICA	SPEC	FLYING LEADS WITH HEAT	SHRINK,	
						2 PLC ±0.25[.010] 3 PLC ±- APPLICA	TION SPEC	ME SWITCH, PUSHBUTTON, HI FLYING LEADS WITH HEAT SEALED, OFF-(ON) AND O	N - () +)	
						4 PLC ±- <u>ANGLES ±5</u> ° − FINISH WEIGHT	S	IZE CAGE CODE DRAWING NO	RESTRICTED	10
				MATERIAL	- -	-	-	C[00119]G=2323333		
					-	- CUSTO	MER DRAWING	SCALE 3:2 SHE	et 3 of 3 rev 1	
	1471-9 (3/13)									

3

4

D

С

В

А

		1			
		REVISIONS			
Р	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

2