



Main

Range of product	8501X
Relay type	Latching
Product or component type	Relay
[In] rated current	10 A AC 5 A DC
Contacts type and composition	8 NO 8 standard contact cartridges
Poles description	8P
[Uc] control circuit voltage	24 V DC
Maximum switching voltage	250 V DC
Mounting support	Panel
Ambient air temperature for operation	-40...160 °F
Electrical connection	Screw clamp terminals
Product certifications	CE CSA UL listed
Operating time	37 ms pick-up 45 ms drop-out

Complementary

Environment

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1332 - Schneider Electric declaration of conformity	Compliant - since 1332 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------