# 9007C54B2Y185112

			۰	
М	V/	2	п	m

Device short name	С
Enclosure type	Standard
Head type	Type C turret head rotary lever
Provided equipment	Receptacle
Series name	Heavy duty

## Complementary

Line Rated Current	10 A	
Body material	Zinc alloy	_
Contact code designation	A600 Q600	
Contacts material	Silver alloy (Ag/Ni)	
Contact operation	Snap action	
Electrical connection	5 STOWA 12 ft pre-wired cable	
Maximum displacement angle	90 °	
Number of connectors	1 green ground connection 1 white 2 black 3 red 4 orange	
Pilot light	Without pilot lamp	_
Specificity of operator	Standard pre-travel	_
Switch actuation	CW and CCW	_
Tilting angle	10°	
Torque value	4 lbf.in	
Tripping angle	4 °	

### **Environment**

ambient air temperature for operation	-20185 °F	
product certifications	CE CSA UL listed	

### Offer Sustainability

Not Green Premium product	Not Green Premium product
Will not be Compliant	Will not be Compliant
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the Stat of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the Star of California to cause birth defects or other reproductive harm	teDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.

For more information go to www.p65warnings.ca.gov For more information go to www.p65warnings.ca.gov

#### Contractual warranty

Warranty period 18 months
---------------------------