





RELEASED FOR PUBLICATION


注記：

- NOTES:

1. APPLICABLE CONTACT P/N : 0-1123721-1
2. MATING CONN P/N: []-1123723-[]
[]-1123724-[]
3. 7-1123722-[] MEET GWT(GLOW WIRE TEST)
750 DEGREE SPEC



断面 A
SECT A

DIMENSIONS: 単位: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED	
		一般公差 ±0.3 >1: 10.4	
MATERIAL 材料 66ナイロン UL94V-0 (66NYLON UL94V-0)		FINISH 仕上 — //	

DWN	24 JUN '98	 TE Connectivity	
N. YAMASAKI			
CHK	24 JUN '98	NAME 名称	
M. SHINDO			
APVD	24 JUN '98	3.96mm PITCH ECONOMY POWER(EP)CONN. PLUG H5G 3.96mm ピッチエコノミーパワー(EP)コネクタ プラグハウジング	
M. SHINDO			
PRODUCT SPEC 製品規格		SIZE 寸法	
108-5609			
APPLICATION SPEC 取付適用規格		CAGE CODE 番号	
—H—			
WEIGHT —H—		DRAWING NO. 図号	
CUSTOMER DRAWING		RESTRICTED TO D1	

参考図面