


SPECIFICATION CONTROL DRAWING

44A014XTITLE
FOUR CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, GENERAL PURPOSE, 600 VOLTDate
28MAR11Revision
F1

This specification sheet forms a part of the latest issue of Raychem Specification 44.

COMPONENT WIRES - 44A011X



CABLE CONSTRUCTION DETAILS

PART NUMBER 1/	CONDUCTOR SIZE (AWG)	OUTSIDE DIAMETER (inches)		MAXIMUM WEIGHT (lb/1000 ft.)
		NOMINAL	MAXIMUM	
44A014X-26-*	26	.082	.098	5.7
44A014X-24-*	24	.097	.115	8.6
44A014X-22-*	22	.114	.134	12.7
44A014X-20-*	20	.133	.156	18.8
44A014X-18-*	18	.157	.183	28.6
44A014X-16-*	16	.174	.205	36.3
44A014X-14-*	14	.215	.253	56.7
44A014X-12-*	12	.261	.306	88.5
44A014X-10-*	10	.312	.363	129.

TEMPERATURE RATING: 150°C

Maximum continuous conductor temperature

VOLTAGE RATING: 600 volts (rms) at sea level

INSULATION FLAWS:

Spark Test, 5.7 kV (rms) at 3 kHz

Impulse Dielectric Test, 8.0 kV (peak)

PART NUMBER:

The "X" in the part numbers above shall be replaced by the applicable conductor material designator as follows:

- 1 tin-coated copper
- 2 silver-coated copper
- 3 nickel-coated copper
- 4 silver-coated high strength copper alloy (AWG's 26-16 only)

The "" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors. Colors shown do not necessarily reflect the sequence of manufacturing.

1/ Example: AWG 20, tin-coated copper wires; black, brown, red and orange component wires:

44A0141-20-0/1/2/3

NOTE: Nominal values are for information only.

Nominal values are not requirements.

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice.
TE Connectivity also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.