

# Electronic housing - ME MAX 22,5 U-U1 GNTQ - 2201189

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Complete housing, length: 99 mm, with vents, Complete housing, Cross connection: DIN rail bus connector, color: green/turquoise, width: 22.5 mm, height: 114.5 mm, number of positions cross connector: 5

#### Your advantages

- Available in overall widths from 6.2 mm to 90 mm, modular extension is possible
- ✓ Inflammability class V0 according to UL 94
- ✓ Variety of connection technologies
- Can be mounted on the DIN rail
- Optional with bus connector for DIN rail mounting as well as power connection system



## **Key Commercial Data**

Packing unit	10 pc
Minimum order quantity	250 pc
GTIN	4 0 4 6 3 5 6 7 4 6 6 9 4
GTIN	4046356746694

## Technical data

#### Standards and Regulations

	,
Flammability rating according to UL 94	V0

### **Environmental Product Compliance**

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Approvals

#### Approvals

#### Approvals

UL Recognized / EAC



# Electronic housing - ME MAX 22,5 U-U1 GNTQ - 2201189

## Approvals

Ex Approvals

### Approval details

UL Recognized http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 240868

EAC [H]

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com