

4805 (3/11)

	2					1			
	DIST	REVISIONS							
АD	00	Р	LTR		DESCRIPTION		DATE	DWN	APVD
			С	REVISED PER	ECO-13-002771		23FEB2013	КН	RP

CONTACT AND SHIELD - PHOS BRONZE HOUSING AND CHICKLET - LCP, UL 94V-0, COLOR - BLACK

CONTACT AREA FINISH CONFORMS TO THE REQUIREMENTS OF TE PRODUCT SPECIFICATION 108-2303; BASED ON

TELCORDIA GR-1217-CORE FOR SYSTEM QUALITY

LEVEL III APPLICATIONS IN CONTROLLED ENVIRONMENTS (CENTRAL OFFICE).

COMPLIANT PIN AREA- 0.5µm MIN MATTE TIN OVER 1.27µm MIN NICKEL. SHIELD I.27µm MIN NICKEL.

 $\boxed{3}$ connector marked on either side of housing with part number, DATE CODE AND STANDARD IN APPROXIMATE AREA SHOWN.

4 dimension applies to centerline of thru hole.

5 DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.

6. CONTACT AREA LUBRICATED WITH BELLCORE APPROVED LUBRICANT. TECHNICAL REFERENCE: GR-1217-CORE, ISSUE I, NOVEMBER 1995.

T REFERENCE APPLICATION SPEC 114-13202 FOR RECOMMENDED PLATED THRU HOLE DIAMETER AND PLATING THICKNESSES.

A THE GROUNDS IN EACH COLUMN ARE COMMENED.

1934276-PART NUMBER

	ONTROLLED DOCUMENT.	S. MAGARO CHK IOMAY2007 W. DAVIS	TE Connectivity
	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±- 1 PLC ±- 2 PLC ±- 3 PLC ±-	APVD 26AUG2008 R.PATTERSON PRODUCT SPEC - APPLICATION SPEC	RECEPTACLE ASSEMBLY, 5 PAIR, 14 COLUMN -
1	4 PLC ±- ANGLES ±- FINISH	-	SIZE CAGE CODE DRAWING NO
	- <u>2</u>	weight _ CUSTOMER DRAWING	$\frac{100779}{\text{C}} = 1934276$