







THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.


REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN-8B0036	2008/09/25	Shin	Add Note
C	LEN1630545	2016/03/17	Ruru	Change Logo
D	CI90269	2019/02/26	Ruru	Modify Note




4Pin Male Connector
Male Pin PCB Layout



Pin Assignments
Front View



Recommenderd Panel Cut-Out



- Note:
- * Important Dimension To Check.
 - * Waterproof Rate: IP67, Unmated
 - * Housing: Thermoplastic, Black
 - * Pin: Copper Alloy, Gold Plated
 - * Nut: Thermoplastic, Black
 - * Gasket: Rubber, Black
 - * Use with waterproof cap or dust cap
Panel Thickness Max: 3.0mm
 - * Use without waterproof cap or dust cap
Panel Thickness Max: 4.0mm
 - * Gasket and Nut are packed separately
in PE bags.

UNIT : mm				TITLE MIDDLE PANEL LOCK 4PIN M CONN. M PIN		Amphenol LTW 安費諾亮泰企業股份有限公司		ITEM NO CB-04PMMP-LC7001		DRAWN BY Ruru		DATE 2019-02-26			
TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°		SCALE 1 : 1		SIZE A4				SHEET 1 OF 1		DWG NO CB-04PMMP-LC7001		CHECKED BY Rita		DATE 2019-02-26	
		REV. D		WC-REV. A.4				QC : Inspection item		CUSTOMER ALTW		APPROVED BY Max		DATE 2019-02-26	